

CIBA-GEIGY CORP -- RP 3266 HARDENER -- 8030-01-126-1431

=====
Product Identification
=====

Product ID:RP 3266 HARDENER

MSDS Date:01/01/1987

FSC:8030

NIIN:01-126-1431

MSDS Number: BBHQK

=== Responsible Party ===

Company Name:CIBA-GEIGY CORP

Address:THREE SKYLINE DRIVE

City:HAWTHORNE

State:NY

Info Phone Num:(914) 347-4700

Emergency Phone Num:(914) 347-4700

CAGE:02684

=== Contractor Identification =

==

Company Name:CIBA SPECIALTY CHEMICALS CORPORATION

Address:4917 DAWN AVE

Box:City:EAST LANSING

State:MI

ZIP:48823-5691

Country:US

Phone:517-351-5900

CAGE:02684

=====
Composition/Information on Ingredients
=====

Ingred Name:AROMATIC HYDROCARBONS (NO DETECTABLE BENZENE)

CAS:70955-17-8

Ingred Name:TRIETHYLENETETRAMINE

CAS:112-24-3

RTECS #:YE6650000

Ingred Name:POLYAMIDE OF C18 FATTY ACID DIMERS & TETA

CAS:68410-23-1

Ingred Name:TRIETHYLENE TRETAMINE POLYMER W/METHYL OXIRAN

E
CAS:26950-63-0

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGESTION: HEATED PRODUCT MAY PRODUCE
INHALABLE VAPORS. SKIN/EYES: IRRITATION & CORROSIVE.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:DANGER CORROSIVE. CAUSES EYE BURNS, SKIN
IRRITATION AND ALLERGIC SKIN REACTIONS.
Medical Cond Aggravated by Expo
sure:SKIN AND EYE IRRITATIONS.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH WATER FOR 15 MIN. SKIN: WASH WITH SOAP AND
WATER. REMOVE CONTAMINATED CLOTHING & LAUNDER BEFORE RE-USE.
INGESTION: IF CONSCIOUS GIVE LARGE QUANTITIES OF WATER. GET MEDICAL
ATTENTION. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN AND/OR
ARTIFICIAL RESPIRATION. IF NEEDED. CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

==

Flash Point Method:CC
Flash Point:193F
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, & WATER.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA)
AND FULL PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY
BE TOXIC.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE SPILLAGE BY ABSORBING IN ABSORBENT
MATERIAL.

=====
Handling and Storage
=====

=====

Handling and Storage Precautions:DANGER COMBUSTIBLE, CORROSIVE-CAUSES EYE BURNS & EYES IRRITATION. KEEP AWAY FROM HEAT & FLAME. DON'T GET IN EYES. AVOID CONTACT WITH SKIN & CLOTHING.

Other Precautions:NUISANCE DUST MAY BE GENERATED WHEN SANDING OR SAWING CURED MATERIAL. AVOID BREATHING VAPOR/MIST. KEEP CONTAINER CLOSED. USE W/ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection

:USE NIOSH APPROVED ORGANIC VAPOR CARTRIDGE RESPIRATOR WHEN VAPOR/MIST.

Ventilation:GENERAL MECHANICAL AND LOCAL EXHAUST.

Protective Gloves:IMPERMEABLE

Eye Protection:WEAR SPLASH-PROOF CHEMICAL GOGGLES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Pres:1.93

Spec Gravity:0.95-0.99

Solubility in Water:SLIGHT

Appearance and Odor:AMBER LIQUID. FINE ODOR

Percent Volatiles by Volume: