

INDUSTRIAL RUBBER CEMENT COMPANY -- LOCK BOND R-35, PART B -- 8040-01-043-3196

=====
Product Identification
=====

Product ID:LOCK BOND R-35, PART B

MSDS Date:01/01/1987

FSC:8040

NIIN:01-043-3196

MSDS Number: BBKJN

=== Responsible Party ===

Company Name:INDUSTRIAL RUBBER CEMENT COMPANY

Address:15257 EAST PROCTOR AVENUE

City:INDUSTRY

State:CA

ZIP:91745

Info Phone Num:(919) 919-8270

Emergency Phone

Num:(213) 333-4578

CAGE:55913

=== Contractor Identification ===

Company Name:INDUSTRIAL RUBBER CEMENT CO

Address:15257 E PROCTOR AVE

Box:City:CITY OF INDUSTRY

State:CA

ZIP:91745-1019

Country:US

CAGE:55913

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN

Other REC Limits:10 MG/CUM (DUST)

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC

:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: IRRITATION & SENSIVITY. TIVITY.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: IRRITATION & SENSITIVITY.

=====
First Aid Measures
=====

First Aid:IN CASE OF CONTACT WITH EYES OR SKIN, IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. IN CASE OF EYE CONTACT, GET MEDICAL ATTENTION. IF MATERIAL HARDENS ON THE SKIN, ALCOHOL IS REQUIRED TO REMOVE IT.

=====
Fire Fighti
=====

ng Measures =====

Flash Point Method:TOC

Flash Point:400F

Extinguishing Media:CO2, DRY CHEMICAL

===== Handling and Storage =====

Handling and Storage Precautions:SOME EPOXY SYSTEMS CAN IRRITATE &
SENSITIZE THE SKIN. AVOID PROLONGED OR REPEATED CONTACT WITHHE
SKIN. USE ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST: ADEQUATE.

Supplemental Safety and Health

=====

===== Physical/Chemical Properties =====

Spec Gravity:10.87

Appearance and Odor:CLEAR VISCOUS, STRAW COLORED. BOTH ARE LIQUIDS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:UNIT PART A AND B ARE MIXED.

Conditions to Avoid Polymerization:WHEN PART A & B ARE MIXED TOGETHER
AN EXOTHERM IS GENERATED.

Disclaimer (provided with this information by the compiling agencies):

This

information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.