View NSN Online: https://aerobasegroup.de/nsn/1377-00-824-2916

Product ID:ACTUATING CARTRIDGE, POWER DEVICE MSDS Date:01/01/1987 FSC:1377 NIIN:00-824-2916 **MSDS Number: BBNWH** === Responsible Party === Company Name: WALTER KIDDE/WILSON, NORTH CAROLINA 27893 Emergency Phone Num: (919) 237-7004 CAGE:EO967 === Contractor Identification === **Company Name: KIDDE INC** WALTER KIDDE DIV AEROSPACE OPNS Address:2500 AIRPORT DRIVE Box:City:WILSON State:NC ZIP:27893-9604 Country:US Phone:252-237-7004 CAGE:61423 Company Name: WALTER KIDDE/WILSON, N.C. 27893 CAGE:EO967

Ingred Name:LEAD AZIDE (SEE SUPPLEMENTAL FOR INGREDIENTS) CAS:13424-46-9 RTECS #:OF8650000

Ingred Name:ZIRCONIUM POWDER RTECS #:ZH7074000 ACGIH TLV:5MG/CUM

Ingred Name:POTASSIUM PERCHLORATE CAS:7778-74-7 RTECS #:SC9700000

Ingred N

ame:BARIUM CHROMATE CAS:10294-40-3 RTECS #:CQ8760000

Ingred Name:LEAD SALTS OF DINITROORTHOCRESYLATE
======================================
Effects of Overexposure: EXPLOSIVE MATERIALS, UPON DETONATION GENERATE NOXIOUS FUMES.
======================================
First Aid:INHALATION: AVOID INHALATION OF FUMES GENERATED DURING DETONATION OF THESE DEVICES. EYES/SKIN: PROTECT FROM DECOMPOSITION PRODUCTS.
====== Fire Fighting Measures ====================================
Extinguishing Media:NONE Fire Fighting Procedures:DON'T FIGHT FIRES. EVACUATE PERSONNEL TO SAFE LOCATION.
Unusual Fire/Explosion Hazard: THESE UNITS CAN EXPLOSIVELY DETONATED BY FIRE/HEAT/IMPACT/ELECTRIC CURRENT/RAPID FREQUENCY ENERGY.
======================================
Spill Release Procedures:CONSULT WITH THE MANUFACTURER TO RECOMMENDED DISPOSAL METHOD.
======================================
Handling and Storage Precautions:STORE IN ACCORDANCE TO REQUIREMENTS OF CFR TITLES 27 & THE NATIONAL FIRE PROTECTION ASSOCIATIOREGULATION. AUTO-IGNITION AT 480F.
Other Precautions: UNITS ARE TO BE HANDLED ONLY BY PERSONS THOROUGHLY TRAINED AND QUALIFIED TO HANDLE EXPLOSIVE DEVICES.
======================================

Respiratory Protection:NOT REQUIRED DURING NORMAL OPERATION. Ventilation:ADEQUATE TO REMOVE NOXIOUS FUMES GE

NERATED DURING NORMAL Protective Gloves:INSULATION Eye Protection:SAFETY GLASSES Other Protective Equipment:STATIC GROUNDING IS RECOMMENDED DURING HANDLING. Supplemental Safety and Health MSDS DATED: 20 MARCH 1986. ALSO CONTAINS: CARBON (FF5250100) 5MG/CUM, TITANIUM (XR2275000).
======================================
Appearance and Odor:METALLIC W/VARIOUS TYPES OF ELEC. CONNECTIONS.
======================================
Stab ility Indicator/Materials to Avoid:YES DON'T ATTEMPT TO OPEN/REMOVE EXPLOSIVE INTERNAL COMPONENTS. Stability Condition to Avoid:EXCESSIVE HEAT/OPEN FLAME/IMPACT/ELECTRIC CURRENTS/RF ENERGY Hazardous Decomposition Products:SHARPNEL/OXIDES OF METAL FUELS/LEAD/TITANIUM/ZIRCONIUM
======================================
Waste Disposal Methods:CONSULT THE INSTITUTE OF EXPLOSIVES MAKERS, WASHINGTON, D.C. FOR ADDITIONAL INFORMATION.
Disclaimer (provided with t his information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.