

DOW CORNING CORP -- 732 MULTI-PURPOSE SEALANT-CLEAR -- 8040-00-225-4548

=====  
Product Identification  
=====

Product ID:732 MULTI-PURPOSE SEALANT-CLEAR

MSDS Date:06/29/1989

FSC:8040

NIIN:00-225-4548

MSDS Number: BBXWG

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW RD

City:MIDLAND

State:MI

ZIP:48686

Info Phone Num:(517) 496-5900

Emergency Phone Num:(517) 496-5900

Preparer's Name:JACK L SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYLTRIACETOXYSILANE, ALKYL TRIACETOXY SILANE

CAS:4253-34-3

RTECS #:VV4500000

Fraction by Wt: 2%

Ingred Name:ETHYLTRIACETOXYSILANE

CAS:17689-77-9

Fraction by Wt: 3%

Ingred Name:S

ILICON DIOXIDE  
CAS:7631-86-9  
RTECS #:VV3100000  
Fraction by Wt: 10%  
OSHA PEL:80 MG/CUM

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: IRRITATION W/REDNESS & SWELLING.  
SKIN: REPEATED/PROLONGED CONTACT (24 TO 48 HRS) MAY IRRITATION.  
INHALATION: IRRITATION TO NOSE & THROAT. INGESTION: LARGE AMOUNTS  
MAY CAUSE DIGESTIVE  
DISCOMFORT.

Explanation of Carcinogenicity:NONE  
Effects of Overexposure:EYES: IRRITATION W/REDNESS & SWELLING. SKIN:  
REPEATED/PROLONGED CONTACT (24 TO 48 HRS) MAY IRRITATION.  
INHALATION: IRRITATION TO NOSE & THROAT. INGESTION: LARGE AMOUNTS  
MAY CAUSE DIGESTIVE DISCOMFORT.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WIPE OFF & FLUSH  
W/WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: OBTAIN MEDICAL  
ATTENTION IN ALL CASES.

=====  
===== Fire Fighting Measures =====

Flash Point Method:OC  
Flash Point:250F  
Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL, FOAM.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & FULL  
PROTECTIVE CLOTHING.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PRODUCT AND USE ABSORBENT MATERIAL TO  
TAKE CARE OF ANY OIL-LIKE RESIDUES.

=====  
===== Handling a

nd Storage =====

Handling and Storage Precautions:STORE