

EASTMAN KODAK CO. -- 189 0755,PHOTOTYPESETTING DEVL & REPL,PT-A -- 6750-00-001-1518

=====
Product Identification
=====

Product ID:189 0755,PHOTOTYPESETTING DEVL & REPL,PT-A

MSDS Date:11/04/1982

FSC:6750

NIIN:00-001-1518

Kit Part:Y

MSDS Number: BCTVZ

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-

5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====
Composition/Information on Ingredients
=====

Ingred Name:POTASSIUM HYDROXIDE (SARA III)

CAS:1310-58-3

RTECS #:TT2100000

Minumum % Wt:2.

Maxumum % Wt:5.

OSHA PEL:C, 2 MG/M3

ACGIH TLV:C 2 MG/M3; 9192

EPA Rpt Qty:1

000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:HYDROQUINONE (SARA III)
CAS:123-31-9
RTECS #:MX3500000
Minumum % Wt:5.
Maxumum % Wt:10.
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:ALKALI SULFITE
Minumum % Wt:15.
Maxumum % Wt:20.

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Minumum % Wt:55.
Maxumum % Wt:65.

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:CONJUNCTIVITIS,CORNEAL BURNS,DEEP SKIN
BURNS,IRRITATION OF RESPIRATORY TRACT,INFLAMM OF LUNGS,EDEMA.

=====
===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR.CALL DOCTOR.REMOVE CONTAMINATED CLOTHING
& SHOES.IN CASE OF CONTACT WITH MATERIAL IMMEDIATELY FLUSH EYES OR
SKIN WITH RUNNING WATER FOR AT LEAST 15 MINUTES.KEEP PATIENT WARM &
QUIE T.EFFECTS OF CONTACT OR INHALATION MAY BE DE
LAYED.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:SMALL FIRES:DRY CHEMICAL OR CO*2,LARGE FIRES:FOAM
OR H*2O
Fire Fighting Procedures:MOVE CONTAINERS FROM FIRE AREA IF WITHOUT
RISK.COOL CONT W/W

=====
===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IF WITHOUT RISK.DO NOT TOUCH SPILLED
MATERIAL.SMALL SPILLS:FLUSH AREA WITH WATER.LARGE SPILLS:DIKE FOR
LATER DISPOSAL,OR

NEUTRALIZE WITH HCL,WIPE WITH MOP OR USE WATER
ASPIRATOR.DRAIN INTO A PPROVED STORAGE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY PLACE TO PREVENT
CORROSION OF SURFACE OF CONTAINER,ABSORPTION OF
MOISTURE,FREEZING,ETC;FOR OUTDOOR AREA IN LIQUID STATE,PROTECT
W/HEATING

Other Precautions:AVOID REPEATED/PROLONGED SKIN CONTACT;THE ROUTINE USE
OF A NON-ALKALINE(ACID)TYPE HAND CLEANER WILL HELP MINIMIZE THE

POSSIBILITY OR ALLERGIC SKIN REACTION;PH APPROX:11.5

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS

Ventilation:AS REQUIRED TO CONTROL MIST,VAPORS IN AIR

Protective Gloves:RUBBER

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:LARGE FACE SHIELD,WORKING CLOTHES.

Supplemental Safety and Health

UNDER CAT #189 0755,ITEM WAS A 2 PARTS KIT;THIS ENTRY DESCRIBES PART A
OF DEVL/REPL;DURING 1986-87,MFR DELETED

CAT #189 0755 & CHANGED THE

2 PART KIT TO SINGLE PART PRODUCT UNDER CAT #100-7913(SEE PNI -C
THIS NSN);KOH PERCENTAGE ON MSDS DTDJUN 23,80 WAS 20-25%,BUT ON
ADDENDUM SHEET DTD 11/2/82 WAS 5-10%,KEY1:B1

=====
===== Physical/Chemical Properties =====

HCC:B1

Boiling Pt:>100.C, 212.F

Vapor Pres:17

Vapor Density:0.6

Spec Gravity:1.30

pH:11.5

Solubility in Water:COMPLETE

Appearance and Odor:OFF-WHITE LIGHT TAN COLOR-NO ODOR.

Percent Volatiles by Volume:80%

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

PER MFR MINERAL ACIDS

Stability Condition to Avoid: UNK

Hazardous Decomposition Products: SULFUR DIOXIDE

Conditions to Avoid Polymerization: UNK

===== Disposal Considerations =====

Waste Disposal Methods: PUT INTO LARGE VESSEL CONTAINING

WATER. NEUTRALIZE WITH HCL. DISCHARGE INTO APPROVED DISPOSAL AREA.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.