

EASTMAN KODAK -- 189 0755,PHOTOTYPESETTING DEVL & REPL,PT-B -- 6750-00-001-1518

=====  
Product Identification  
=====

Product ID:189 0755,PHOTOTYPESETTING DEVL & REPL,PT-B

MSDS Date:11/04/1982

FSC:6750

NIIN:00-001-1518

Kit Part:Y

MSDS Number: BCTWB

=== Responsible Party ===

Company Name:EASTMAN KODAK

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Emergency Phone Num:716-722-515

1

CAGE:5K871

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ACETIC ACID (SARA II

l)  
CAS:64-19-7  
RTECS #:AF1225000  
Fraction by Wt: 50-55%  
OSHA PEL:10 PPM  
ACGIH TLV:10 PPM/15 STEL; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:1-PHENYL-3-PYRAZOLIDINONE  
CAS:92-43-3  
RTECS #:UQ8750000  
Fraction by Wt: 5-10%

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 34-45%

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Haz  
ards Acute and Chronic:CAUSE IRRITATION,BURNS.  
Effects of Overexposure:INH:VAP IRRIT;EYES:VAP IRRIT.LIQUID CONTACT  
CAUSES BURNS;SKIN:LIQUID CONTACT CAUSES SEVERE BURNS.

=====  
First Aid Measures  
=====

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED  
ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED  
HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN.FOR BURNS GET  
MED ATTN.REMOVE CON TAMINATED CLOTHING WHILE WASHING C  
ONTMNTD AREA.

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Extinguishing Media:CO\*2,DRY CHEM  
Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT  
W/WATER SPRAY.  
Unusual Fire/Explosion Hazard:NONE KNOWN

=====  
Accidental Release Measures  
=====

Spill Release Procedures:EVACUATE UNPROTECTD PERSONS.ELIM IGN  
SOURCES.USE PROTECTV EQUIP.PROVIDE VENT.STOP LEAK W/O RISK.DIKE LG  
SPILL & PUMP INTO COVRD DRUMS;

ABSORB/CONTAIN SM SPILL IN CONTNR

PENDNG DISPOSAL;MFG RECOMM,NEUTR LZ W/BICARBONATE & FLUSH TO SEWER  
W/H\*2OIAW REGS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM STRONG ALKALI.STORE IN  
COOL,DRY PLACE.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM  
PHYSICAL DAMAGE.AVOID CONTACT WITH ALKALIS

Other Precautions:AVOID SKIN/EYE CONTACT W/CHEMICAL PRODUCTS.WASH  
THOROUGHLY AFTER HANDLING.PH OF PROD:212F/>100C

Vapor Pres:16

Vapor Density:1.4

Spec Gravity:1.07

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID-VINEGAR ODOR.

Percent Volatiles by Volume:97%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

PER MFR AVOID ALKALIS;FLAMMABLE/OXIDIZING MATL.

Stability Condition to Avoid:UNK

Hazardous Decomposition Products:NONE KNOWN

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN

COVERED CONTNRS PENDG DISPOSAL.SHIP

WASTE MATL TO NEUTRALIZNG/DISPOSAL FACILITY IAW DOT/EPA

REGS.HANDLE/DISPOSE OF IAW FED,STATE/LOCAL REGS;MFGR RECOMM

NEUTRLIZE W/BICARBONATE & FLUSH TO SEWER W/LG AMT H\*2O IAW EXISTNG  
REGS & CHECKCOLOR CODE

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warran

ts this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.