

FULLER H B CO -- SC-1185,SOLVENT CEMENT -- 8040-00-058-2399

===== Product Identification =====

Product ID:SC-1185,SOLVENT CEMENT

MSDS Date:01/01/1985

FSC:8040

NIIN:00-058-2399

MSDS Number: BCWMZ

=== Responsible Party ===

Company Name:FULLER H B CO

Address:315 S HICKS RD

City:PALATINE

State:IL

ZIP:60067-6940

Country:US

CAGE:7P551

=== Contractor Identification ===

Company Name:FULLER H B CO

Address

:315 S HICKS RD

Box:City:PALATINE

State:IL

ZIP:60067-6940

Country:US

CAGE:7P551

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 11%.

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 29%.

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 40%.

OSHA PEL:100 PPM

===== Hazards Identification =====

Effects of Overexposure:VAPOR: HEADACHE, NAUSEA, DIZZINESS, IMPAIRMENT OF COORD.

===== First Aid Measures =====

First Aid:INHAL: MOVE TO FRESH AIR, GIVE ART RESP IF NEC. CALL MD.

SKIN: REMOVE W/SOAP & WATER. EYE: IMMEDIATELY FLUSH W/WATER FOR 15 MIN & CALL

MD. INGEST: CALL MD. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point: