

CORONADO PAINT COMPANY, INC. -- PRIMER COATING, 37875 WHITE -- 8010-00-059-8822

=====
Product Identification
=====

Product ID:PRIMER COATING, 37875 WHITE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-059-8822

MSDS Number: BCWPR

=== Responsible Party ===

Company Name:CORONADO PAINT COMPANY, INC.

CAGE:33200

=== Contractor Identification ===

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY RO

AD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====
Composition/Information on Ingredients
=====

Ingred Name:PIGMENTS

Fraction by Wt: 52%

Ingred Name:LINSEED & ALKYD RESINS

Fraction by Wt: 26%

Ingred Name:AROMATIC & ALIPHATIC HYDROCARBONS

Fraction by Wt: 20%

ACGIH TLV:100PPM

Ingred Name:LEAD NAPHTHENATE

Fraction by Wt: 0.5%

=====
Hazards Identification
=====

Effects of Overexposure:SEVERE EYE IRRI

TATION, DRYING OF SKIN.

EXCESSIVE INHALATION CAUSES HEADACHE, DIZZINESS, NAUSEA.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH MILD SOAP AND WATER AND APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH AIR AND CALL A PHYSICIAN. APPLY ARTIFICIAL RESPIRATION IF NECESSARY.

=====
Fire Fighting Measures
=====

Flash Point:90F, SETA

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:

FOAM, CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures:TREAT AS CLASS B FIRE.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR A RESPIRATOR. FLUSH WITH WATER INTO RETAINING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS, FIRE OR HOT METAL SURFACES.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN

FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED

CONTACT WITH SKIN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:SELF CONTAINED NIOSH APPROVED PROTECTION IF TLV IS EXCEEDED

Ventilation:LOCAL EXHAUST

Protective Gloves:YES

Eye Protection:YES

Other Protective Equipment:EYE BATH AND SAFETY SHOWER

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC

:F4
Boiling Pt:B.P. Text:240F
Vapor Pres:6
Vapor Density:3.7
Spec Gravity:1.35
Evaporation Rate & Reference:0.7, BUAC=1
Solubility in Water:VERY SLIGHT
Appearance and Odor:WHITE OPAQUE LIQUID, PETROLEUM DISTILLATE ODOR
Percent Volatiles by Volume:38

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES OR FIRE
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL, INCINERATION UNDER SAFE AND SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.