

HARRY MILLER CORP -- STEELGUARD MS-31 -- 8030-00-062-5866

=====  
Product Identification  
=====

Product ID:STEELGUARD MS-31

MSDS Date:01/01/1985

FSC:8030

NIIN:00-062-5866

MSDS Number: BCWTG

=== Responsible Party ===

Company Name:HARRY MILLER CORP

Address:4TH AND BRISTOL ST

City:PHILADELPHIA

State:PA

ZIP:19140

Country:US

CAGE:EO427

=== Contractor Identification ===

Company Name:HARRY MILLER CORPORATI  
ON

CAGE:EO427

Company Name:MILLER HARRY CORP

Address:4TH AND BRISTOL ST

Box:City:PHILADELPHIA

State:PA

ZIP:19140

Country:US

CAGE:07648

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 50%

OSHA PEL:100 PPM

Ingred Name:SODIUM PETROLEUM SULFONATE

Fraction by Wt: 5-10%

Ingred Name:WAX, OXIDIZED HYDROCARBON

30-40%

Ingred Name:INERT FILLERS

Fraction by Wt: 2%

ACGI

H TLV:2 MG/CUM (MFR)

=====  
Hazards Identification  
=====

Effects of Overexposure:HEADACHE OR DIZZINESS.

=====  
First Aid Measures  
=====

First Aid:INGESTION: DO NOT INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. SKIN & EYE: FLUSH W/ WATER FOR 15 MINUTES.

=====  
Fire Fighting Measures  
=====

Flash Point:105F; 41C, COC  
Lower Limits:0.8  
Upper Limits:5  
Extinguishing Media:CO\*2, FOAM, DRY  
CHEMICAL  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ELIMINATE IGNITION SOURCE. ABSORB WITH INERT MATERIAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT & FLAMES. AVOID CONTACT WITH EYES & SKIN.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NIOSH/MSH  
A APPROVED RESPIRATOR IF REQUIRED  
Ventilation:LOCAL EXHAUST RECOMMENDED TO KEEP BELOW TLV.  
Protective Gloves:RECOMMENDED  
Eye Protection:SAFETY GLASSES  
Other Protective Equipment:NONE  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:F4  
Boiling Pt:B.P. Text:310F; 154C  
Vapor Density:> 1  
Spec Gravity:1  
Evaporation Rate & Reference:1 (ETHER= 1)  
Solubility in Water:INSOLUBLE  
Appearance and Odor:BROWN LIQUID  
Percent Volatiles by Volume:50

==

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

===== Disposal Considerations =====

Waste Disposal Methods: MANUFACTURER RECOMMENDS INCINERATION. DISPOSAL METHODS MUST BE IAW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in n

o manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.