

PENRECO DIVISION, PENNZOTL -- PETROTECT AMBER, CODE 4040 -- 8030-00-062-5866

=====
Product Identification
=====

Product ID: PETROTECT AMBER, CODE 4040

MSDS Date: 01/01/1985

FSC: 8030

NIIN: 00-062-5866

MSDS Number: BCWTL

=== Responsible Party ===

Company Name: PENRECO DIVISION, PENNZOTL

Address: 700 MILIAM ST PENNZOIL PL

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

CAGE: JO941

=== Contractor Identif

ication ===

Company Name: PENRECO DIVISION, PENNZOTL

Address: 700 MILIAM ST PENNZOIL PL

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

CAGE: JO941

Company Name: PENRECO, DIV OF PENNZOIL CO

Address: 700 MILIAM ST

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

Phone: 800-245-3952

CAGE: 86459

=====
Composition/Information on Ingredients
=====

Ingred Name: STODDARD SOLVENT

CAS: 8052-41-3

RTECS #: WJ8925000

Fraction by Wt: 58.5%

OSHA PEL: 500 PPM

ACGIH TLV: 100 PPM; 9293

=====

==== Hazards Identification =====

Effects of Overexposure:EYE: BURNING/IRRIT. SKIN: IRRIT/DERMATITIS.
INHAL: LOCAL IRRIT,DROW,COMA/PHEUMONIA(SEE SUP DATA)

==== First Aid Measures =====

First Aid:EYE: FLUSH W/ WATER FOR AT LEAST 15 MIN,CALL DOCTOR IMMED.
SKIN: REMOVE CONTAMINATED CLOTHING WASH EXPOSED AREA W/ SOAP &
WATER,WASH CONTAMINATED CLOTHING BEFORE REUSE. INHAL: REMOVE TO FRESH
AIR IMMED. APPLY ARTIFICIAL RESP
IF NEC (SEE SUP DATA)

==== Fire Fighting Measures =====

Flash Point:100F;38C; TCC
Lower Limits:1
Upper Limits:6
Extinguishing Media:CO*2,DRY CHEM,FOAM
Fire Fighting Procedures:USE WATER ONLY TO COOL CANS OF
FLAM/COMBUSTIBLE MATERIALS.
Unusual Fire/Explosion Hazard:CONTACT W/ ACID/ACID FUMES/HEATED TO
DECOMPOSITION WILL EMIT TOXIC FUMES OF SO*X

==== Accidental Release Measures =====

Spill Release Procedures:PROVIDE ADEQU
ATE VENT,REMOVE IGNITION
SOURCES,AVOID PROLONGED INHAL OF FUMES & LONG TERN SKIN
CONTACT,AVOID EYE CONTACT. FLUSH SPILL W.WATER OR SWEEP UP W/
ABSORBENT MATERIAL;STORE IN COVERD METALLIC MARKED CANS & DISPOSE
AS SOON AS POSSIBLE

==== Handling and Storage =====

Handling and Storage Precautions:FLAM & COMBUSTIBLE LIQUID KEEP AWAY
FROM SOURCES OF IGNITION. KEEP CANS CLOSED. PROVIDE ADEQUATE VENT,
USE IN ATMOSPHERE OF INERT GAS INSTEAD O
F AIR
Other Precautions:DO NOT TRANSFER TO UNMARKED CONTAINERS. CONTAINER: 1
GALLON.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESP PROTECTION FOR PARTICULAR
EXPOSURE OF CONCERN
Ventilation:RECOMMENDED TO KEEP BELOW TLV.
Protective Gloves:RUBBER
Eye Protection:SFTY GOG W/FACE SHIELD
Other Protective Equipment:RUBBER PROTECTIVE CLOTHING:
BOOTS,APPRONS;ETC.
Supplemental Safety and Health
SPEC: AM 2 GR4. EFFECTS OF OVE

REXPOSURE: INGEST: LOCAL IRRIT OF MUCOUS
EMBRANES, MOUTH, THROAT, ESOPHAGUS, STOMACH EMERGENCY PROCEDURE;
INGEST: DO NOT INUCE VOMIT CALL DOCTOR IMMED.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300-325F

Vapor Pres: