View NSN Online: https://aerobasegroup.de/nsn/9150-00-065-0115

## DELTA PETROLEUM CO., INC -- AIRCRAFT PISTON ENGINE OIL,MIL-L-22851C,II -- 9150-00-065-0115

Product ID:AIRCRAFT PISTON ENGINE OIL,MIL-L-22851C,II

MSDS Date:05/16/1990

FSC:9150

NIIN:00-065-0115

MSDS Number: BCWZV === Responsible Party ===

Company Name: DELTA PETROLEUM CO., INC

Address:800 RIVER ROAD

City:ST. ROSE

State:LA ZIP:70087 Country:US

Info Phone Num:303-289-4483 - DENVER, COLORADO

Emergency Phone Num:504-467-1399 - ST. ROSE, LOUISIANA

Preparer's Name: J.R. SWOAP

CAGE:7A348

=== Contractor Identification ===

Company Name: DELTA PETROLEUM CO., INC

Address:10352 RIVER ROAD,

Box:10397 City:ST. ROSE

State:LA ZIP:70087 Country:US

Phone:504-832-2732

CAGE:7A348

======= Composition/Information on Ingredients ========

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC

CAS:64742-65-0

RTECS #:PY8038500

Fraction by

Wt: 30 - 35%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name: HYDROTREATED C25 BRIGHT STOCK BASED LUBRICATING OIL

CAS:72623-83-7

Fraction by Wt: 55 - 60%

Other REC Limits: NONE SPECIFIED

Ingred Name: ADDITIVES PACKAGE

Fraction by Wt: 8 - 12%

Other REC Limits: NONE SPECIFIED

======== Hazards Identification ==============

LD50 LC50 Mixture:LD50 (ORAL RAT) IS >5,000 MG/KG Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:EYES/SKIN:MINIMALLY
IRRITATING.INHALATION:MINIMALLY IRRITATING IF NOT IN EXCESS OF 5
MG/M3 (OIL MIST).INGESTION:LOW LEVEL OF TOXICITY.CHRONIC:NONE
SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity: ONLY USED MOTOR OILS WERE SHOWN TO CAUSE SKIN CANCER WHEN TESTED ON MICE.

Effects of Overexposure:MAY CAUSE EYE, SKIN & RESPIRATORY TRACT IRRITATION. LOW LEVEL OF TOXICITY, IF SWALLO WED.

First Aid:INHALATION:NONE CONSIDERED NECESSARY.EYE:FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN.GET MEDICAL ATTENTION IF IRRITATION PERSISTS.SKIN:NONE CONSIDERED NECESSARY.INGESTION:NONE CONSIDERE D NECESSARY.

============ Fire Fighting Measures =========================

Flash Point Method:COC
Flash Point:490F,254C
Extinguishing Media: USE WATER FOG CAR

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, "ALCOHOL" FOAM, OR

DRY CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING. Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:NONE ========= Accidental Release Measures ============ Spill Release Procedures: CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB ON SUITABLE MATERIAL AND SHOVEL UP. Neutralizing Agent: NONE SPECIFIED BY MANU FACTURER. ============= Handling and Storage ================= Handling and Storage Precautions: STORE IN A COOL DRY PLACE. PERIODS OF EXPOSURE TO HIGH TEMPERATURES SHOULD BE MINIMIZED.WATER CONTAMINATION SHOULD BE AVOIDED. Other Precautions: AVOID SKIN CONTACT WITH USED MOTOR OILS. USED MOTOR OILS HAVE CAUSED SKIN CANCER IN LABORATORY ANIMALS.IN CASE OF SKIN CONTACT, PROMPTLY WASH THOROUGHLY WITH SOAP AND WATER. OIL-SOILED CLOTHING SHOULD BE CLEANED BEFORE REUSE. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED RESPIRATORS AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS. RESPIRATORY PROTECTION NOT ORDINARILY R EQUIRED. Ventilation: ROOM VENTILATION IS ADEQUATE. Protective Gloves: NEOPRENE RUBBER AS REQUIRED. Eve Protection: SAFETY GLASSES RECOMMENDED. Other Protective Equipment: EYE WASH STATION AND SAFET Y SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED. Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR. Supplemental Safety and Health MISUSE OF EMPTY CONTAINERS CAN BE HAZARDOUS. CUTTING OR WELDING OF

MISUSE OF EMPTY CONTAINERS CAN BE HAZARDOUS. CUTTING OR WELDING OF EMPTY CONTAINERS MIGHT CAUSE FIRE, EXPLOSION OR TOXIC FUMES FROM RESIDUES. DO NOT PRESSURIZE OR EXPOSE TO OPEN FLAME OR HEAT.KEEP CON TAINER CLOSED.

======= Physic

HCC:V6 Spec Gravity:0.8871 Appearance and Odor:BRIGHT AND CLEAR, MILD
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:HIGH TEMPERATURES AND OPEN FLAMES Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES AND KETONES, COMBUSTION PRODUCTS OF NITROGEN AND SULFUR
========= Disposal Considerations ==============

Waste Disposal Methods:PRODUCT HAS BEEN EVALUATED FOR RCRA CHARACTERISTICS AND DOES NOT MEET CRITERIA OF A HAZARDOUS WASTE IF DISCARDED IN ITS PURCHASED FORM.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person uti lizing this

al/Chemical Properties ========

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.