

DEVCON CORP -- RUST-LICK 606;RUST PREVENTIVE,SOLVENT BASE -- 6850-00-066-2334
===== Product Identification =====

Product ID:RUST-LICK 606;RUST PREVENTIVE,SOLVENT BASE

MSDS Date:02/20/1987

FSC:6850

NIIN:00-066-2334

MSDS Number: BCXBP

=== Responsible Party ===

Company Name:DEVCON CORP

Address:30-ENICOTT STREET

City:DANVERS

State:MA

ZIP:01923-3753

Country:US

Info Phone Num:617-777-1100

Emergency Pho

ne Num:617-777-1100

CAGE:16059

=== Contractor Identification ===

Company Name:DEVCON CORP

Address:30 ENDICOTT ST

Box:City:DANVERS

State:MA

ZIP:01923-3753

Country:US

Phone:1-508-777-1100

CAGE:16059

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM SOLVENT

CAS:64742-47-8

Fraction by Wt: 70.0%

OSHA PEL:5MG/CUM,OIL MIST

ACGIH TLV:5MG/CUM,OIL MIST

Ingred Name:HEXYLENE GLYCOL

CAS:107-41-5

RTECS #:SA0810000

Fraction by Wt: 5G/KG;DERMAL >3.16G/KG

Routes of Ent

ry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:MILD IRRITANT TO EYES AND
SKIN;IRRITATION TO RESPIRATORY TRACT;MAY CAUSE HEADACHES,DIZZINESS
AN ANESTHETIC EFFECTS.CHRONIC:NOT KNOWN.
Explanation of Carcinogenicity:NO

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER FOR 15 MINUTES,CONTACT A
PHYSICIAN.SKIN:WASH WITH SOAP AND WATER.INGEST:DO NOT IND
UCE
VOMITING.CONTACT MD IMMEDIATELY.IF VOMITING OCCURS,KEEP HEAD BELOW
HIPS TO PREVENT ASPIRATION OF LIQ IN LUNGS.INHAL:REMOVE TO FRESH
AIR.

=====
===== Fire Fighting Measures =====

Flash Point:175F,79C COC
Lower Limits:0.6
Upper Limits:7.0
Extinguishing Media:CO*2,DRY CHEMICAL,FOAM
Fire Fighting Procedures:USE SUPPLIED-AIR BREATH EQUIP IN ENCLOSED OR
CONFINED AREAS.
Unusual Fire/Explosion Hazard:NONE(PER MFR)

=====
===== Accidental Release
Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES,VENTILATE
AREA.USE NONCOMBUSTIBLE ABSORBENT MATERIAL TO CONFINE SPILL.CLEAN
UP AREA.DISCARD IN SUITABLE CONTAINERS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,OPEN FLAMES AND
OTHER IGNITION SOURCES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIR

ATOR FOR ORGANIC

VAPORS IF ABOVE TLV/PEL.

Ventilation:GENERAL VENTILATION ADEQUATE

Protective Gloves:NEOPRENE

Eye Protection:SPLASH-PRF GOG,SIDE SHLDS

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO PREVENT
PRLG SKIN CONTACT

Work Hygienic Practices:AVOID CONTACT WITH EYES,SKIN AND CLOTHES,DO NOT
BREATHE VAPORS/MIST:DO NOT USE CONTAMINATED CLOTHES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P.

Text:>390F,199C

Vapor Pres:5

Spec Gravity:0.84

pH:7.0

Evaporation Rate & Reference: