

ILLINOIS BRONZE PAINT COMPANY -- WEEKEND SPRAY PAINT -- 8010-00-079-3762

=====  
Product Identification  
=====

Product ID:WEEKEND SPRAY PAINT

MSDS Date:01/01/1985

FSC:8010

NIIN:00-079-3762

MSDS Number: BCXRL

=== Responsible Party ===

Company Name:ILLINOIS BRONZE PAINT COMPANY

Emergency Phone Num:312-438-8201

CAGE:91794

=== Contractor Identification ===

Company Name:ILLINOIS BRONZE PAINT COMPANY

Addr

ess:300 EAST MAIN STREET

City:LAKE ZURICH

State:IL

ZIP:60047-2580

Country:US

Phone:800-228-5635

CAGE:91794

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYLENE CHLORIDE (DICHLOROMETHANE) (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 37%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM; Z-2

ACGIH TLV:50 PPM, A2; 9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 5%

ACGIH

TLV:500 PPM

Ingred Name:VM&P NAPHTHA  
RTECS #:ZB1600000  
Fraction by Wt: 6%  
ACGIH TLV:500 PPM

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 14%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:PROPELLANT

===== Hazards Identification =====

Effects of Overexposure:INHAL-ANESTHETIC; IRRITATE RESPIR. TRACT OR  
NERVOUS SYST. DIZZINESS. EYE & SKIN - PRIMARY IRRITANT.

===== First Aid Measures =====

First Aid:FUMES- REMOVE TO FRESH AIR. EYES-FLUSH W LGE AMTS WATER FOR  
AT LEAST 15 MIN. GET MEDICAL ATTENTION SKIN-WIPE W TOWEL; REMOVE  
REMAINDER W MIN. SPIRITS, TURPENTINE OR LACQUER THINNER. WASH WITH  
SOAP & WATER. REMOVE CONTAMINATED CLOTHING.

===== Fire Fighting Measures =====

Flash Point:-40F, -40C  
Lower Limits:0.8  
Extinguishing Media:DRY CHEM, CO2, FOAM NFPA CLASS B EXTINGUISHER.  
Fire Fighting Procedures:CANS WILL RUPTURE (190F) & DISCHARGE FLAMMABLE  
CONTENTS  
Unusual Fire/Explosion Hazard:WATER MAY BE INEFFECTIVE EXCEPT TO COOL  
CLOSED CONTAINERS. WEAR GOGGLES & SELF-CONT BREATH APPARATUS

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
BREATHING VAPORS. VENTILATE AREA. REMOVE W INERT ABSORBENT.

===== Handling and Storage =====

Handling and

Storage Precautions:DO NOT STORE ABOVE 120F. STORE LGE  
QUANTITIES IN BLDG DESIGNED FOR NFPA CLASS 1A FLAMMABLE LIQUIDS.  
Other Precautions:DO NOT SPRAY IN EYES. DO NOT PUNCTURE OR INCINERATE  
CANS. DO NOT STICK SHARP OBJECTS IN TOP OPENING. DO NOT FLAME CUT,  
BRAZE OR WELD WO USBM APPROVED RESPIRATOR OR ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Ventilation:KEEP CONC BELOW TLV & BELOW LEL IF WELDING OR FLAME  
CUTTING.

Protective Gloves

:NONE

Eye Protection:NO SPECIAL

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:42-391F

Vapor Density:>AIR

Evaporation Rate & Reference:>ETHER(PROP)