

PRATT & LAMBERT-WICHITA DIV. -- 745-406 -- 8010-00-081-0809

=====
Product Identification
=====

Product ID:745-406

MSDS Date:01/01/1985

FSC:8010

NIIN:00-081-0809

MSDS Number: BCXVM

=== Responsible Party ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Emergency Phone Num:316-733-1361

CAGE:KO010

=== Contractor Identification ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Box:2153

CAGE:KO010

Company Name

:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 5.35%

OSHA PEL:0.05 MG/M3;1910.1025

ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 45.0%

OSHA PEL:100 PPM

=====

==== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTHETIC & IRRITATION TO AIRWAY;IRRITATION-SKIN/EYE.HEADACHE,DIZZY,COMA.

==== First Aid Measures =====

First Aid:FLUSH SKIN/EYES WITH PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING. INHAL:REMOVE TO FRESH AIR. CALL MD.IF NEEDED.

==== Fire Fighting Measures =====

Flash Point:104 F, 40 C, TCC

Lower Limits:1.1

Extinguishing Media:C

ARBON DIOXIDE/DRY CHEM.SMALL;POLYMER FOAM-LARGE
FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE FOR FIREMEN.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE DUE TO PRESSURE BUILD-UP.

==== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAME,SPARKS...). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

====

==== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE AMTS.IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions:DO NOT INGEST.GROUND CONTAINERS WHEN POURING.AVOID FREE FALL OF A FEW INCHES. DO NOT FLAME CUT,BRAZE,OR WELD COATED MATERIAL W/O VENTILATION.

==== Exposure Controls/Personal Protection =====

Respiratory Pr

Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR OF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO
CONTAMINATED CLOTHING.

Supplemental Safety and Health

BOILING RANGE 155-189C.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-373 F

Evaporation Rate & Refer
ence:< ETHER

Appearance and Odor:DARK GREEN PAINT.

Percent Volatiles by Volume:60.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IAW LOCAL,STATE AND FED.REGULATIONS.
INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED
CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.