

THREE BOND OF AMERICA,INC. -- ANAETOBIC SEALANT PRIMER,GRADE T,YELLOW --
8040-00-082-2508

===== Product Identification =====

Product ID:ANAETOBIC SEALANT PRIMER,GRADE T,YELLOW

MSDS Date:01/01/1987

FSC:8040

NIIN:00-082-2508

MSDS Number: BCYBC

=== Responsible Party ===

Company Name:THREE BOND OF AMERICA,INC.

Emergency Phone Num:213-879-9143

CAGE:60859

=== Contractor Identification ===

Company Name:

THREE BOND OF AMERICA,INC.

Address:20815 HIGGINS COURT

Box:City:TORRANCE

State:CA

ZIP:90501

Country:US

Phone:310-320-3342

CAGE:60859

===== Composition/Information on Ingredients =====

Ingred Name:1,1,2-TRICHLOROETHANE (SARA III)

CAS:79-00-5

RTECS #:KJ3150000

Fraction by Wt: 60.0%

OSHA PEL:S, 10 PPM

ACGIH TLV:S, 10 PPM; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 30.0%

OSHA PEL:S

,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 9.0%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:HYDROGEN PEROXIDE (SARA III)
CAS:7722-84-1
RTECS #:MX0900000
Fraction by Wt: 1.0%
OSHA PEL:1 PPM
ACGIH TLV:1 PPM; 9192

=====
===== Hazards Identification =====
=====

Effects of Overexposure:EYE/SKIN IRRITANT.POTENTIAL SKIN SENSITIZER.

=====
===== First Aid Measures =====
=====

First Aid:SKIN:FLUSH WITH WATER. EYES:FLUSH WITH WATER FOR AT LEAST 15
MIN.CALL DR. WASH SOILED CLOTHES BEFORE RE-USE.DISCARD CONTAMINATED
SHOES.

=====
===== Fire Fighting Measures =====
=====

Flash Point:>200 F, 93 C CC
Extinguishing Media:FOAM,CO*2 OR DRY CHEM.,WATERSPRAY
Fire Fighting Procedures:COOL ALL CONTAINERS NOT
IGNITED WITH FIRE
HOSES
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:AVOID EYE AND SKIN CONTACT,OR ORAL
INGESTION,WEAR PROTECTIVE EQUIP.WASH AREA WELL AND COLLECT MATERIAL
FOR INCINERATION.

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions:STORE IN A COOL PLACE OUT OF DIRECT
SUNLIGHT.CHANGE OF CLOTHING SHOULD BE AVAILABLE.AT END OF SHIFT

WORKER SHOULD SHOWER TO REMOVE VAPORS FROM PORES.
Other Precautions:FIRE FIGHTERS MUST WEAR SELF-CONTAINED AIR
SUPPLY.SHOES SHOULD BE AIRED OUT DAILY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL VENTILATION REQUIRED.
Ventilation:LOCAL EXHAUST,NORMAL VENTILATION ADEQUATE
Protective Gloves:IMPERVIOUS
Eye Protection:CHEM.SAFETY GOGGLES
Other Protective Equipment:IMPERVIOUS OVER SHOES AND PROTECTIVE
CLOTHING
Supplemental Safety and
Health

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:185 F 85 C
Evaporation Rate & Reference:< ETHER
Appearance and Odor:YELLOW PRIMER
Percent Volatiles by Volume:99.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:NO
Stability Condition to Avoid:OPEN FLAME
Hazardous Decomposition Products:CO AND CO*2

===== Disposal Considerations =====

Waste D
isposal Methods:CHEM.INCINERTOR

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this informa

tion to their
particular situation.