

GOODYEAR AEROSPACE CORP/AKRON, OH 44315-0001 -- INSULATOR, #9536207 --  
1630-00-106-6794

===== Product Identification =====

Product ID:INSULATOR, #9536207

MSDS Date:01/01/1987

FSC:1630

NIIN:00-106-6794

MSDS Number: BCYWM

=== Responsible Party ===

Company Name:GOODYEAR AEROSPACE CORP/AKRON, OH 44315-0001

Emergency Phone Num:(216) 796-2121

CAGE:EO533

=== Contractor Identification ===

Company Name:GOO

DYEAR AEROSPACE CORPORATION

Address:1210 MASSILLON ROAD

City:AKRON

State:OH

ZIP:44315

Phone:(216) 796-2121

CAGE:EO533

Company Name:LORAL CORP DEFENSE SYSTEMS DIV-AKRON

Address:1210 MASSILLON RD

Box:City:AKRON

State:OH

ZIP:44315-0001

Country:US

Phone:216-796-2800

CAGE:25500

===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS (CHRYSTILE) 65-70%

RTECS #:GC2625000

Fraction by Wt: 70%

ACGIH TLV:2.0 FB/CC

Ingred Name:PHENOL-FORMALDEHYDE RESIN 26-35%

Fraction b

y Wt: 35%

=====  
Hazards Identification  
=====

Effects of Overexposure:CHRONIC OVEREXPOSURE TO AIRBORNE CONCENTRATIONS OF ASBESTOS MAY LEAD TO ASBESTOSIS & MESOTHELIOMA

=====  
First Aid Measures  
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ADVICE. SKIN: WASH WITH SOAP & WATER. EYE: FLOOD WITH WATER. IF IRRITATION OCCURS, SEE A PHYSICIAN. INGESTION: CONSULT A PHYSICIAN. CHANGE CLOTHING, IF NECESSARY/AVOID DUSTS PARTICLES IN OTHER AREAS

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Fire Fighting Procedures:COMBUSTION PRODUCTS OF THIS MATERIAL MAY BE TOXIC. USE SCBA.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:VACUUM OR WET CLEAN IF DUST IS INVOLVED. VACUUM SYSTEM SHOULD BE EQUIPPED WITH AN OUNET HEPA FILTER TO PREVENT REINTRODUCING ASBESTOS FIBERS TO THE ATMOSPHER

=====  
Handling and Storage  
=====

Handling and Storage Precautions:HANDLE TO MINIMIZE FORMATION OR RETENTION OF DUST.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:IF >TLV, A NIOSH/MSHA APPROVED RESPIRATOR FOR ASBESTOS.  
Ventilation:LOCAL EXHAUST VENTILATION IS RECOMMENDED  
Eye Protection:SAFETY GOGGLES/FACE SHIEL  
Supplemental Safety and Health  
MSDS DATE: 4/85

=====  
Physical/Chemical Properties  
=====

=====

HCC:T7

Boiling Pt:B.P. Text:NONE

Solubility in Water:0

Appearance and Odor:DARK BROWN SOLID

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DUST SHOULD BE HANDLED AS HAZARDOUS AIR  
POLLUTANT IN ACCORDANCE W/40 CFR 61 SUBPART M PERTAINING TO  
ASBESTOS. USE LANDFILLS FOR ASBESTOS DISPOSAL. SCRAP PA  
RTS ARE NOT  
FRIABLE AND ARE NOT RESTRICTED UN DER AIR POLLUTION REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume r  
esponsibility for the suitability of this information to their  
particular situation.