

DAVIS-HOWLAND OIL CORPORATION -- MIL-L-21260C; LUBRICATING OIL -- 9150-00-111-0211  
===== Product Identification =====

Product ID:MIL-L-21260C; LUBRICATING OIL

MSDS Date:01/01/1987

FSC:9150

NIIN:00-111-0211

MSDS Number: BCZBK

=== Responsible Party ===

Company Name:DAVIS-HOWLAND OIL CORPORATION

Emergency Phone Num:(716)473-6650

CAGE:FO626

=== Contractor Identification ===

Company Name:DAVIS HOWLAND  
OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Phone:(716) 473-6650

CAGE:FO626

===== Composition/Information on Ingredients =====

Ingred Name:LUBRICATING OIL (TAKE TLV AS OILMIST)

ACGIH TLV:5MG/CUM(OILMIST)

Ingred Name:PRESERVATIVE (TYPE NOT SPECIFIED)

ACGIH TLV:NOT SPECIFIED

===== Hazards I

dentification =====

Effects of Overexposure:MAY CAUSE IRRITATION OF EYES,SKIN AND UPPER  
RESPIRATORY TRACT;INGEST:NAUSEA,HEADACHE AND VOMITING.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF  
NEED;EYES/SKIN:FLUSH W LG AMTS H\*2O FOR 15 MIN;INGEST:RINSE MOUTH;  
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER  
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Meas  
ures =====

Flash Point:47OF/243C (COC)

Lower Limits:1.0

Upper Limits:4.0

Extinguishing Media:FOAM,DRY CHEMICAL,CO\*2,OR WATER FOG OR SPRAY

Fire Fighting Procedures:COOL CONTRS WITH WATER SPRAY.USE NIOSH/MSHA  
APPROVED SCBA.

Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE WITH STRONG OXIDANTS  
LIKE LIQUID CHLORINE OR CONC O\*2.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION:RECOVER FREE  
LIQU

ID;USE SUITABLE ABSORBENT MATERIAL AND RECOVER FOR PROPER  
DISPOSAL

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED  
AREA.KEEP AWAY FROM HEAT,SPARKS,FLAMES OR STRONG OXIDANTS.KEEP  
CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:AVOID CONTACT WITH SKIN AND EYES.DO NOT BREATHE  
VAPORS OR MIST.DO NOT USE CONTAMINATED CLOTHES.WASH THOROUGHLY  
AFTER EACH USE.

===== Exposure Contr

ols/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR OIL MIST/VAPORS IF ABOVE TLV

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

MSDS IS UNDATED:ITEM IS GRADE 50 OF THE SPEC:MIL-L-21260C

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:670F/354C

Vapor Pres:12

Spec Gravity:0.88

Evaporation Rate & Reference:< 0.01 (NO REF)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DARK COLORED FLUID WITH MILD PETROLEUM ODOR

Percent Volatiles by Volume:NEGL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS LIKE CL\*2,CONC.O\*2,OR HYPOCHLORITE

Stability Condition to Avoid:HEAT,OPEN FLAME,SPARKS.

Hazardous

Decomposition Products:FUMES,CO,CO\*2,SMOKE AND SULFUR OXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information

mation to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.