

BULK CHEMICAL DIST, INC. -- MIL-C-16173D, CORROSION PREVENTATIVE, CLII -- 8030-00-118-0666

=====  
Product Identification  
=====

Product ID:MIL-C-16173D, CORROSION PREVENTATIVE, CLII

MSDS Date:01/01/1985

FSC:8030

NIIN:00-118-0666

MSDS Number: BCZRL

=== Responsible Party ===

Company Name:BULK CHEMICAL DIST, INC.

Emergency Phone Num:(504) 362-3232

CAGE:EO174

=== Contractor Identification ===

Company N

ame:BULK CHEMICAL DIV,MALTER INTERNATIONAL

Address:80 FIRST ST

City:GRETNA

State:LA

ZIP:70053

Country:US

CAGE:EO174

Company Name:BULK CHEMICALS DISTRIBUTORS,INC

Address:80 FIRST STREET

City:GRETNA,

State:LA

ZIP:70053

Country:US

Phone:504-362-3232 DISCONNECTED(2-20-92)

CAGE:56921

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 75%.

OSHA PEL:100 PPM

=====  
Hazar

ds Identification =====

Effects of Overexposure:INH: ANESTH IRRIT TO RESP TRACT OR ACUTE CNS  
DEPR CHAR BY HDCH, DIZZ, STAG, CNFSN, UNCON, COMA.

===== First Aid Measures =====

First Aid:INH: MOVE TO FRESH AIR. RESTORE BRTHNG, CALL MD. SKIN: FLUSH  
IMMED W/RUNNING WATER, CALL MD. IF IRRIT PERSISTS. EYE: IMMED FLUSH  
W/WATER AT LEAST 15 MIN, CALL MD IMMED.

===== Fire Fighting Measures =====

Flash  
Point:100F TCC  
Lower Limits:0.8  
Extinguishing Media:NFPA CLASS B EXTINGUISHER, CO\*2, DRY CHEM  
Fire Fighting Procedures:USE RESP. WATER INEFF ON FIRE, USE TO COOL  
CNTNRS.  
Unusual Fire/Explosion Hazard:CLOSED CNTNRS MAY EXPLODE IF EXPOSED TO  
EXTREME HEAT. VAP MAY CAUSE VIOLENT EXPLOSIONS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENT AREA.  
AVOID BRTHNG VAPORS, USE RESP IN ENCLOSED AREA. REMOVE W/INER  
T  
ABSORBENT. USE NONSPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE >120F. STORE LG QTY IN  
BLDGS DESIGNED & PROT FOR STG OF NFPA CLASS I COMBUSTIBLE LIQ.  
AVOID PROLONGED SKIN CNTCT.  
Other Precautions:SKIN/EYE CNTCT W/PROD PRODUCES PRIMARY IRRIT. CNTNR  
SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL IN EXCESS OF FEW  
IN. USE ADEQUATE VENT OR RESP PROT.

===== Exposure Controls/Personal  
Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESP PROT FOR PARTICULAR  
EXPOSURE OF CONCERN  
Ventilation:LOCAL EXHST, ADEQUATE TO KEEP BELOW TLV/LEL  
Protective Gloves:YES  
Eye Protection:YES  
Other Protective Equipment:PREVENT PROLONGED SKIN CNTCT W/CONTAM  
CLOTHING  
Supplemental Safety and Health  
VAPOR DENSITY: HEAVIER THAN AIR. KEEP CONTAINERS TIGHTLY CLOSED. DO NOT  
APPY TO HOT SURFACES. PRODUCT CONFORMS TO MIL-C-16173D, CLASS II

===== Physical/Chemi

cal Properties =====

HCC:V3

NRC/State Lic Num:NA

Boiling Pt:B.P. Text:310 TO 387F

Vapor Pres:2.0

Spec Gravity:0.80

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR AMBER

Percent Volatiles by Volume:75.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

===== Disposal Considerations =====

Waste Disposal Me

thods:STORE ABSORBENT IN CLOSED CNTNR. MFR SUGGESTS

SANITARY LANDFILL OR INCINERATION IAW LOCAL, STATE, FED REG.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent profess

ional advice to verify and

assume responsibility for the suitability of this information to their particular situation.