View NSN Online: https://aerobasegroup.de/nsn/8030-00-138-1761

Product ID:PL-106, PART A, #2777010 MSDS Date:01/01/1987 FSC:8030 NIIN:00-138-1761 **MSDS Number: BDBHX** === Responsible Party === Company Name: BF GOODRICH ADHESIVE SYS/AKRON, OH 44318 Emergency Phone Num: (216) 374-3422 CAGE:BFGAD === Contractor Identification === Company Name: BF GOODRICH ADHES **IVE SYSTEMS** Address:123 WEST BARTGES ST. D/1932/1904 City:AKRON State:OH ZIP:44311 Country:US Phone:216-374-2824(CLIFF PEARSON) CAGE:BFGAD Company Name: BF GOODRICH CO Address:3925 EMBASSY PKY Box:5471 City:AKRON State:OH ZIP:44313-0471 Country:US Phone:216-374-3985 CAGE:25472

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 30% OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 15% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:GLYCOL ETHER ACETATE Fraction by Wt: 10%

Ingred Name:EPOXY Fraction by Wt: 15%

Ingred Name:ZINC CHROMATE CAS:13530-65-9 RTECS #:GB3290000 Fraction by Wt: 15% OSHA PEL:0.1 MG/M3 (CRO3) ACGIH TLV:0.01MG/M3(CR)A1;9192

====== Hazards Ide

Effects of Overexposure:INHALATION: HEADACHE/NAUSEA/LOSS OF COORDINATION/DIZZINESS/UNCONSCIOUSNESS/EVEN ASPHYXIATION.

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: REMOVE CONTAMINATED CLOTHING/LAUNDER BEFORE REUSE. WASH AFFECTED AREA W/SOAP & WATER. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES. INGESTION: DO NOT INDUCE VOMITI NG. CALL A PHYSICIAN IMMEDIATELY.

Flash Point:20F TCC Lower Limits:1.4% Extinguishing Media:WATER FOG, CO2, FOAM, DRY CHEMICAL Fire Fighting Procedures: DON'T ENTER CONFINED AREA W/OUT PROTECTIVE EQUIPMENT SCBA. Unusual Fire/Explosion Hazard: VAPOR MAY BUILD UP IN POORLY VENTILATED AREAS/BE IGNITED, CAUSING FLASH FIRES OR EXPLOSIONS. Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES, PROVIDE ADEQUATE VENTILATION, AVOID BREATHING VAPORSAVOID EYE/SKIN CONTACT. WIPE UP WITH RAGS/PAPER/OTHER ABSORBENT. PLACE ISUITABLE CLOSED CONTAINERS FOR DISPOSAL. Handling and Storage Precautions: USE ONLY IN A WELL VENTILATED AREA. ELIMINATE ALL SOURCES OF IGNITION SUCH AS SPARKS/FLAMES/NOEXPLOSION PROOF DEVICES. Other Precautions: AVOID PROLONGED/REPEATED SKIN CONT OR BREATHING OF VAPORS. KEEP OUT OF THE REAC H OF CHILDREN. STORE IN TIGHTLY CLOSED CONTAIR, IN A COOL DRY PLACE, AWAY FROM ALL SOURCES OF **IGNITION/HEAT** Respiratory Protection:>TLV, USE NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS. Ventilation: PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV Protective Gloves: IMPERVIOUS Eye Protection: CHEMICAL GOGGLES Supplemental Safety and Health MSDS DATE: 19 FEB 86, WGT PER GAL: 8.31 PDS. KEY1:F3. HCC:F2 Boiling Pt:B.P. Text:175-410F Vapor Density:>AIR Evaporation Rate & amp; Reference: N-BUTYL ACETATE Appearance and Odor: GREEN COLORED LIQUID WITH AROMATIC ODOR. Percent Volatiles by Volume:68% Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Hazardous Decomposition Products:CO2, CO, SMOKE, ALIPHATICS AND OTHERS.

====== Disposal Considerat

Waste Disposal Methods: THIS MATERIAL IS DISCARDED. IS HAZARDOUS/MUST BE PROPERLY STORED, TRANSPORTED. DISPOSED OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and di

sclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.