

BF GOODRICH ADHESIVE SYS -- PL-106, PART A, #2777010 -- 8030-00-138-1761

=====
Product Identification
=====

Product ID:PL-106, PART A, #2777010

MSDS Date:01/01/1987

FSC:8030

NIIN:00-138-1761

MSDS Number: BDBHX

=== Responsible Party ===

Company Name:BF GOODRICH ADHESIVE SYS/AKRON, OH 44318

Emergency Phone Num:(216) 374-3422

CAGE:BFGAD

=== Contractor Identification ===

Company Name:BF GOODRICH ADHES

IVE SYSTEMS

Address:123 WEST BARTGES ST. D/1932/1904

City:AKRON

State:OH

ZIP:44311

Country:US

Phone:216-374-2824(CLIFF PEARSON)

CAGE:BFGAD

Company Name:BF GOODRICH CO

Address:3925 EMBASSY PKY

Box:5471

City:AKRON

State:OH

ZIP:44313-0471

Country:US

Phone:216-374-3985

CAGE:25472

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 30%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200

PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:GLYCOL ETHER ACETATE
Fraction by Wt: 10%

Ingred Name:EPOXY
Fraction by Wt: 15%

Ingred Name:ZINC CHROMATE
CAS:13530-65-9
RTECS #:GB3290000
Fraction by Wt: 15%
OSHA PEL:0.1 MG/M3 (CRO3)
ACGIH TLV:0.01MG/M3(CR)A1;9192

=====
Hazards Identification =====

Effects of Overexposure:INHALATION: HEADACHE/NAUSEA/LOSS OF
COORDINATION/DIZZINESS/UNCONSCIOUSNESS/EVEN ASPHYXIATION.

=====
First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: REMOVE CONTAMINATED
CLOTHING/LAUNDER BEFORE REUSE. WASH AFFECTED AREA W/SOAP & WATER.
EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES. INGESTION: DO NOT
INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.

=====

=====
Fire Fighting Measures
=====

Flash Point:20F TCC

Lower Limits:1.4%

Extinguishing Media:WATER FOG, CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:DON'T ENTER CONFINED AREA W/OUT PROTECTIVE EQUIPMENT SCBA.

Unusual Fire/Explosion Hazard:VAPOR MAY BUILD UP IN POORLY VENTILATED AREAS/BE IGNITED, CAUSING FLASH FIRES OR EXPLOSIONS.

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES, PROVIDE ADEQUATE VENTILATION, AVOID BREATHING VAPORS/AVOID EYE/SKIN CONTACT. WIPE UP WITH RAGS/PAPER/OTHER ABSORBENT. PLACE ISUITABLE CLOSED CONTAINERS FOR DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:USE ONLY IN A WELL VENTILATED AREA. ELIMINATE ALL SOURCES OF IGNITION SUCH AS SPARKS/FLAMES/NOEXPLOSION PROOF DEVICES.

Other Precautions:AVOID PROLONGED/REPEATED SKIN CONT OR BREATHING OF VAPORS. KEEP OUT OF THE REAC
H OF CHILDREN. STORE IN TIGHTLY CLOSED
CONTAIR, IN A COOL DRY PLACE, AWAY FROM ALL SOURCES OF
IGNITION/HEAT

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:>TLV, USE NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL GOGGLES

Supplemental Safety and Health

MSDS DATE: 19 FEB 86, WGT PER GAL: 8.31 PDS. KEY1:F3.

=====
Physical/Chemical Properties
=====

HCC:F2

Boiling Pt:B.P. Text:175-410F

Vapor Density:>AIR

Evaporation Rate & Reference:N-BUTYL ACETATE

Appearance and Odor:GREEN COLORED LIQUID WITH AROMATIC ODOR.

Percent Volatiles by Volume:68%

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:CO2, CO, SMOKE, ALIPHATICS AND OTHERS.

=====
Disposal Considerat

ions =====

Waste Disposal Methods: THIS MATERIAL IS DISCARDED. IS HAZARDOUS/MUST BE PROPERLY STORED, TRANSPORTED. DISPOSED OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and di

sclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.