

DOW CORNING CORP -- 3145 RTV ADHESIVE SEALANT-GRAY -- 8040-00-144-9774

=====
Product Identification
=====

Product ID:3145 RTV ADHESIVE SEALANT-GRAY

MSDS Date:09/11/1993

FSC:8040

NIIN:00-144-9774

MSDS Number: BDBZJ

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:SOUTH SAGINAW RD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:517-496-5900

Preparer's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:METHOXYSILANE (TLV BASED ON METHANOL FORMED DUR)

NG
CURING-MFR)
Fraction by Wt: 4%
ACGIH TLV:200 PPM

=====
Hazards Identification
=====

Effects of Overexposure:EYE:IRRIT,PAIN,RED,POSS MINOR CORNEAL
INJURY.SKIN:RPTD,PRLNG EXP POSS SLIGHT IRRIT. (SEE SUPP DATA)

=====
First Aid Measures
=====

First Aid:EYES:FLUSH W/PLENTY OF H*2O FOR @ LEAST 15 MIN. SKIN:WIPE OFF
& FLUSH W/H*2O. INHAL:NO PROBLEM (MFR). ORAL:NO PROBLEM (MFR).

=====
Fire Fighti
ng Measures
=====

Flash Point Method:CC
Flash Point:>212F,>100C
Extinguishing Media:H*2O FOG,CO*2,DRY CHEMICAL,FOAM
Fire Fighting Procedures:NIOSH/MSHA APPROVED SCBA & PROTECTIVE CLTHG
SHOULD BE WORN.
Unusual Fire/Explosion Hazard:NONE KNOWN TO DOW CORNING

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE PRODUCT & USE ABSORBENT MATERIAL TO
TAKE CARE OF ANY OIL-LIKE RESIDUES. USE PROPER PROTECTION-SAFETY
GLASSES,AS
A MINIMUM.USE RESPIRATORY PROTECTION IF NECESSARY.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE BELOW 90F(32C).WASH AT MEALTIME
& END OF SHIFT.USE REASONABLE CARE & CAUTION.
Other Precautions:PRODUCT LIBERATES METHANOL IF EXP TO H*2O/HUMID
AIR.PROVIDE ADEQUATE VENT DURING PROCESS TO PREVENT METHANOL VAPORS
ABOVE 200 PPM. DATE OF PREP:10-04-85. U/I:12 OZ CARTRIDGE.

=====
Exposure Controls/Personal Protection =

=====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation:MECHANICAL RECOMMENDED;LOCAL EXHAUST MAY BE NEEDED.

Protective Gloves:IMPERMEABLE(FPN

Eye Protection:CHEMICAL WORKERS GOGGLES

Other Protective Equipment:AS REQUIRED LOCALLY.

Supplemental Safety and Health

INHAL:NO INJURY LIKELY FROM SHORT EXP.INGEST:SMALL AMT INGESTED FROM NORMAL USE NOT HARMFUL.NO KNOWN ADVERSE CHRONIC HLTH EFTS.MAY ENHANCE ALLERGIC CONDTN IN SOME PEO
PLE BUT NONE KNOWN.

===== Physical/Chemical Properties =====

HCC:T6

Spec Gravity:1.12

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GRAY, PASTE-LIKE; SWEET ODOR.

Percent Volatiles by Volume: