

BATTENFELD -- MIL-L-46017(MR) CODE 60037-300 LUB OIL -- 9150-00-145-0112

=====
Product Identification
=====

Product ID:MIL-L-46017(MR) CODE 60037-300 LUB OIL

MSDS Date:09/01/1988

FSC:9150

NIIN:00-145-0112

MSDS Number: BDCCV

=== Responsible Party ===

Company Name:BATTENFELD

Address:1575 CLINTON ST

City:BUFFALO

State:NY

ZIP:14206

Info Phone Num:716-822-8410

Emergency Phone Num:716-822-8410

Preparer

's Name:THOMAS G MUSILLI

CAGE:60229

=== Contractor Identification ===

Company Name:BATTENFELD

Box:728

City:NORTH TONAWANDA

State:NY

ZIP:14120

Country:US

Phone:716-695-2100

CAGE:60229

Company Name:BATTENFELD GREASE AND OIL CORP OF NEW YORK INC

Address:1174 ERIE AVE

Box:728

City:NORTH TONAWANDA

State:NY

ZIP:14120-3036

Country:US

Phone:716-695-2100

CAGE:60226

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (DISTILLATES,SOLVENT-DEWAXED HEAVY PARAFFINIC)

CAS:64742-65-0
RTECS #:PY8038500
Fraction by Wt: 50%
OSHA PEL:5MG/M*3(MIST)
ACGIH TLV:5MG/M*3(MIST)

Ingred Name:MINERAL OIL
CAS:72623-83-7
Fraction by Wt: 44%
OSHA PEL:5MG/M*3(MIST)
ACGIH TLV:5MG/M*3(MIST)

Ingred Name:POLYISOBUTYLENE
CAS:9003-27-4
RTECS #:UD1010000
Fraction by Wt: 2%

Ingred Name:SULFORIZED ISOBUTYLENE
CAS:68511-50-2
Fraction by Wt: 1%

Ingred Name:LARD-METHYL ESTER
CAS:68082-78-0
Fraction by Wt: 3%

===== Hazards Identification =====

Report
s of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SEE SIGNS & SYMPTOMS OF OVEREXPOSURE.
Explanation of Carcinogenicity:MANUFACTURER STATES NO CARCINOGENIC OR
MUTAGENIC INGREDIENTS.
Effects of Overexposure:EYES/SKIN:MILD EYE & SKIN IRRITATION;NO
SENSITIZATION & NO CORROSIVE EFFECTS.
Medical Cond Aggravated by Exposure:NONE NOTED.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER FOR 15 MINUTES.GET MEDICAL

ATTENTION;SKIN:FLUSH WITH WATER.REMOVE & LAUNDER CONTAMINATED CLOTHING;INHALATION:N/R;INGESTION:DO NOT INDUCE VOMIT.GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:360F(182C)
Autoignition Temp:Autoignition Temp Text:400F
Extinguishing Media:WATER FOG,CO*2,DRY CHEMICAL,FOAM,EARTH OR SAND.
Fire Fighting Procedures:WEAR SCBA. WATER MAY CAUSE FROTHING.
Unusual Fire/Explosion Hazard:NONE

===== A
ccidental Release Measures =====

Spill Release Procedures:SWEEP OR SCOOP UP & REMOVE. ABSORB WITH SAND OR INERT MATERIAL. PLACE IN APPROPRIATE DISPOSAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED PLACE,LOW FIRE RISK AREA. KEEP CONTAINERS CLOSED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WITH ADEQUATE VENTILATION.
Ventilation:GENERAL (MECHANICAL) VENTILATION
Protective Gloves:NEOPRENE,POLYETHYLENE
Eye Protection:FACE SHIELD
Other Protective Equipment:NONE
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. REMOVE & LAUNDER CONTAMINATED CLOTHING.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:700F(371C)
Spec Gravity:0.89
Solubility in Water:NEGLIGIBLE
Appearance and Odor:FLUID. TACKY OIL. FATTY ODOR.
Percent V

Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS.

Stability Condition to Avoid: HEAT, SPARKS, OPEN FLAMES

Hazardous Decomposition Products: CO, CO*2

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE. COMPLY WITH ALL APPLICABLE
FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This info

rmation is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.