

DOW CORNING CORP -- 33 EXTREME LOW TEMPERATURE BEARING GREASE, LIGHT --  
9150-00-145-0161

===== Product Identification =====

Product ID:33 EXTREME LOW TEMPERATURE BEARING GREASE, LIGHT

MSDS Date:11/11/1992

FSC:9150

NIIN:00-145-0161

MSDS Number: BDCDB

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone

Num:517-496-6000

Emergency Phone Num:517-496-5900

Preparer's Name:JACK L. SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETH

TOWN  
State:KY  
ZIP:42701-9804  
Country:US  
Phone:502-737-6757  
CAGE:66172

=====  
Composition/Information on Ingredients  
=====

Ingred Name:2,6-CIS-DIPHENYLHEXAMETHYLCYCLOTETRASILOXANE  
CAS:33204-76-1  
RTECS #:GZ4390000  
Fraction by Wt: 121C  
Lower Limits:NOT GIVEN  
Upper Limits:NOT GIVEN  
Extinguishing Media:WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, FOAM  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &  
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE.  
Unusu  
al Fire/Explosion Hazard:TOXIC GASES ARE RELEASED DURING  
COMBUSTION.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE PRODUCT AND USE ABSORBENT MATERIAL TO  
TAKE CARE OF ANY OIL-LIKE RESIDUES.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH  
ADEQUATE VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH  
TEMPERATURES.  
Other Precautions:AVOID SKIN CONTACT. LAUNDER CONTAMINATED CLOTHING  
BEFORE REUSE.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NOT NORMALLY REQUIRED.  
Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION TO  
MAINTAIN EXPOSURE LEVELS.  
Protective Gloves:NOT NORMALLY REQUIRED.  
Eye Protection:SAFETY GLASSES OR GOGGLES  
Other Protective Equipment:AN EMERGENCY EYE WASH STATION AND SHOWER  
SHOULD BE AVAILABLE.  
Work Hyg

Hygienic Practices: WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT  
AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING. USE AT ELEVATED  
TEMPERATURES OR AEROSOL/SPRAY APPLICATIONS MAY REQUIRE ADDED  
PRECAUTIONS. TRACES OF BENZENE AND FORMALDEHYDE MAY FORM IF HEATED  
IN AIR ABOVE 300F. PROVIDE VENTILATION TO CONTROL VAPOR EXPOSURES  
WITHIN INHALATION GUIDELINES AT ELEVATED TEMPERATURES.

===== Physica

/Chemical Properties =====

HCC:V6

Boiling Pt: B.P. Text: NOT GIVEN

Melt/Freeze Pt: M.P/F.P Text: NOT GIVEN

Vapor Pres: < 5

Vapor Density: NOT GIVEN

Spec Gravity: 1.05

Evaporation Rate & Reference: NOT GIVEN

Solubility in Water: NEGLIGIBLE

Appearance and Odor: LIGHT BEIGE-TAN GREASE, VERY LITTLE ODOR

Percent Volatiles by Volume: