View NSN Online: https://aerobasegroup.de/nsn/9350-00-153-6816

J.H.FRANCE REFRACTORIES CO. -- HYDRECON 3000 CASTABLES-FIRECLAY, HEAVY WT

9350-00-153-6816

============= Product Identification ========================

Product ID:HYDRECON 3000 CASTABLES-FIRECLAY,HEAVY WT

MSDS Date:11/19/1985

FSC:9350

NIIN:00-153-6816

MSDS Number: BDCWK === Responsible Party ===

Company Name: J.H.FRANCE REFRACTORIES CO.

Address:1956 FRANCE RD

City:SNOW SHOE

State:PA ZIP:16874 Country:US

Emergency Phone Nu m:(814)387-6811

Preparer's Name: I.DULBERG, TECHNICAL MGR

CAGE:KO332

=== Contractor Identification ===

Company Name: FRANCE J H REFRACTORIES CO

Address:1956 FRANCE RD Box:City:SNOW SHOE

State:PA ZIP:16874 Country:US

Phone:814-355-5076

CAGE:07316

Company Name: J.H.FRANCE REFRACTORIES CO.

Address:1956 FRANCE RD. Box:City:SNOW SHOE

State:PA ZIP:16874 Country:US CAGE:KO332

======= Composition/Information on Ingredients ========

Ingred Name: SILICA, AMORPHOUS, DUST

CAS:112945-52-5

RTECS #:V

CAS:65997-16-2 ============ Hazards Identification ========================= Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHALATION OF ALL DUSTS ARE HAZARDOUS. CRYSTALLINE SILICA WHEN INHALED MAY CAUSE SILICOSIS. THIS IS A CHRONIC SLOWLY DEVELOPING LUNG DISEASE. THE CEMENT BINDER MAY CAUSE EYE AND SKIN BURNS. Explanation of Carcinogenicity:NOT LISTED Effect s of Overexposure: SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure: ANY MEDICAL CONDITION AFFECTING SAME ORGANS AS THOSE AFFECTED BY OVEREXPOSURE. First Aid:TERMINATE EXPOSURE. MOVE TO FRESH AIR. FLUSH AFFECTED EYES & SKIN WITH WATER. CONSULT PHYSICIAN IF NECESSARY. Extinguishing Media: NON-COMBUSTIBLE. USE EXTINGUISHING MEDIA **APPROPRIATE** TO SURROUNDING FIRE. ======== Accidental Release Measures ============ Spill Release Procedures: SWEEP UP & PLACE IN SUITABLE DISPOSAL CONTAINERS. ============= Handling and Storage ========================== Handling and Storage Precautions: AVOID INHALATION OF DUST. PROTECT EYES & SKIN. Other Precautions: CONSULT WITH MANUFACTURER ON CURING, DRYING, AND FIRING INSTRUCTIONS. ====== Exposure Controls/Personal Protection ======== Respiratory Prot

V7310000

OSHA PEL:6 MG/M3

ACGIH TLV:10 MG/M3; 8990

Ingred Name: CEMENT BINDER

ection:NIOSH APPROVED DUST MASK.