

FEL-PRO INC -- C-661 ANTISEIZE LUBRICANT -- 8030-00-155-6444

===== Product Identification =====

Product ID:C-661 ANTISEIZE LUBRICANT

MSDS Date:01/01/1985

FSC:8030

NIIN:00-155-6444

MSDS Number: BDCXV

=== Responsible Party ===

Company Name:FEL-PRO INC

Address:7450 N MCCORMICK

City:SMOKIE

State:IL

ZIP:60076-4046

Country:US

CAGE:FO660

=== Contractor Identification ===

Company Name:FEL-PRO INC

Address

:7450 N MCCORMICK BLVD

Box:C1103

City:SKOKLE

State:IL

ZIP:60076

Phone:(312) 674-7700

CAGE:FO660

Company Name:FEL-PRO INC DIV OF FELT PRODUCTS MFG CO

Address:7450 N MCCORMICK

Box:1103

City:SKOKIE

State:IL

ZIP:60076-4046

Country:US

Phone:847-674-7700 OR 312-761-4500

CAGE:73165

===== Composition/Information on Ingredients =====

Ingred Name:REFINED STRAIGHT CHAIN & CALCIUM SOAP-MODIFIED NAPHTHENIC
MINERAL OILS. CAS 64742-53-6

Fraction by Wt: 54.8%

ACGIH TLV:10 MG/CUM

Ingred

Name:GRAPHITE (TLV GIVEN FOR TOTAL DUST; SAME FOR 1000661NO)
RTECS #:VV7780000
Fraction by Wt: 37.6%
ACGIH TLV:10 MG/CUM

Ingred Name:AMORPHOUS SILICON DIOXIDE
Fraction by Wt: 2.3%
ACGIH TLV:20 MPPCF

Ingred Name:ALUMINUM (SARA III)
CAS:7429-90-5
RTECS #:BD0330000
Fraction by Wt: 1.7%
OSHA PEL:15MG/M3 DUST/5 FUME
ACGIH TLV:10MG/M3 DUST; 9192

=====
Hazards Identification
=====

Effects of Overexposure:NONE EXPECTED; POSSIBLE REDNESS OR IRRITATION OF SKIN OR EYES IF PROLONGED, REPEATED CONTACT IN SENSITIVE INDIVIDUALS

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH TEPID WATER 15 MIN, HOLDING EYELIDS APART. CALL MD; SKIN: WASH WITH SOAP & WATER. IF IRRITATION OCCURS, CALL MD; INHALATION: REMOVE TO FRESH AIR, KEEP WARM & QUIET. CONSULT MD.

=====
Fire Fighting Measures
=====

Flash Point:310 F (COC)
Extinguishing Media:USE CO₂, FOAM, DRY CHEMICAL OR WATER FOG
Fire Fighting Procedures:DO NOT DIRECTLY POUR WATER INTO FIRE. USE SELF-CONTAINED BREATHING APPARATUS IN CONFINED AREA. NONE EXCEPT AS FOR PETROLEUM GREASE FIRES.

=====
Accidental Release Measures
=====

Spill Release Procedures:WIPE UP WITH RAGS OR ABSORBENT MATERIAL. COMPLETE CLEANUP USING DETERGENT & WATER OR USE CHLORINATED SOLVENT OR HIGH FLASH POINT SOLVENT CLEANER WITH ADEQUATE VENTILATION TO AVOID POSSIBLE INHALATION INJURY OR FIRE.

=====
Handling and Storage
=====

orage =====

Handling and Storage Precautions:NORMAL STORAGE & HNDLNG. AVOID EXPOSURE TO IGNITION SOURCES, H1 HEAT OR OPEN FLAMES.
Other Precautions:KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQD W/ADEQUATE VENTILATION
Ventilation:LOCAL-PREFERBLE (50 FPM);GENERAL-ACCEPTABLE (50-FPM)(MFG REC
Protective Gloves:NONE NECESSARY
Eye Protection:SUFFICIENT TO PRVNT CNTCT
Other Protective Equipment:NONE NECESSARY
Supplemental Safety and Health
MFG LISTS % VOLATILE BY VOL. TO BE NEGLIGIBLE. NOT A 2 PART PRODUCT.
MFGR MAKES 2 PROD UNDER THIS NSN NO.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:570-780 F
Vapor Pres:1
Spec Gravity:1.15
Evaporation Rate & Reference:NEGLIGIBLE N-BU AC
Solubility in Water:INSOLUBLE
Appearance and Odor:DARK GREY PASTE, SLIGHT PETROLATUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZERS (NITRIC ACID, PEMANGANATES, PEROXIDES
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:PYROLYSIS YIELDS CO, CO*2 & COMPLETELY BURNED HYDROCARBONS

===== Disposal Considerations =====

Waste Disposal Methods:CONTROLLED INCINERATION OR BURY IN A POSTED TOXIC SUBSTANCES LANDFILL SITE IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided

with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.