

TRIAD PAINT & CHEMICAL CORP -- TT-V-51 -- 8010-00-160-5856

=====
Product Identification
=====

Product ID:TT-V-51

MSDS Date:01/01/1985

FSC:8010

NIIN:00-160-5856

MSDS Number: BDDHZ

=== Responsible Party ===

Company Name:TRIAD PAINT & CHEMICAL CORP

Emergency Phone Num:212-443-2778

CAGE:JO907

=== Contractor Identification ===

Company Name:TRIAD PAINT & CHEMICAL CORP.

Address:810 EVERGREEN AVENUE

Box:

NA

City:BROOKLYN

State:NY

ZIP:11207

Country:US

Phone:(718) 443-2278

CAGE:JO907

Company Name:TRIAD PAINT AND CHEMICAL CORP

Address:810 EVERGREEN AVE

Box:City:BROOKLYN

State:NY

ZIP:11207-1140

Country:US

CAGE:33151

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS

Fraction by Wt: 58.0%

ACGIH TLV:200 PPM

=====
Hazards Identification
=====

Effects of Overexposure:ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUID
IS MILDLY

TO MODERALLY EYE IRRITATING

=====
First Aid Measures
=====

First Aid: REMOVE VICTIM AND RESTORE BREATHING IF NECESSARY. WASH SKIN WITH SOAP AND WATER. FLUSH EYES WITH COLD WATER

=====
Fire Fighting Measures
=====

Lower Limits: 1.0

Upper Limits: 6.0

Extinguishing Media: FOSM, CO₂, STEAM WATER FOG, DRY CHEMICAL

Fire Fighting Procedures: DO NOT USE WATER, EXCLUDE AIR

Unusual Fire/Explosion Hazard: VAPOR FORMS EXPLOSIVE MIXTURE BETWEEN

UPPER AND LOWER EXPLOSIVE LIMITS

=====
Accidental Release Measures
=====

Spill Release Procedures: AVOID FLAME AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION

=====
Handling and Storage
=====

Handling and Storage Precautions: AVOID OPEN FLAME AND SPARK SOURCES. AVOID SPLASH FILLING. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: ORGANIC CANNISTER MASK, OR AIR PACK

Ventilation: APPROVED CLASS D EXPLOSION PROOF MOTOR AND SWITCHES

Protective Gloves: SOLVENT RESISTANT

Eye Protection: CONVENTIONAL EYE COVER

Supplemental Safety and Health

BOILING RANGE 157-194C

=====
Physical/Chemical Properties
=====

Boiling Pt: B.P. Text: 315-382F

Vapor Density: 5.0

Spec Gravity: .78

Evaporation Rate & Reference: BUTYL ACETATE .13

Solubility in Water: NEGLIGIBLE

Appearance and Odor: BLACK COLORED LIQUID

UID, HYDROCARBON ODOR
Percent Volatiles by Volume:65.8

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CO, CO*2 WHEN COMBUSTED

===== Disposal Considerations =====

Waste Disposal Methods:EVAPORATE OR FLUSH WITH COLD WATER IN A WELL
VENTILATED AREA. USE OIL SEWER IF AVAILABLE, OR REMOVE TO A
CONTAINER

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.