

TRUETECH INC (FORM CHEM COMPOUNDING CORP) -- PAINT,FACE,CAMOUFLAGE,STICK FORM --
6850-00-161-6202

===== Product Identification =====

Product ID:PAINT,FACE,CAMOUFLAGE,STICK FORM

MSDS Date:02/01/1995

FSC:6850

NIIN:00-161-6202

MSDS Number: BDDL B

=== Responsible Party ===

Company Name:TRUETECH INC (FORM CHEM COMPOUNDING CORP)

Address:680 ELTON AVE

City:RIVERHEAD

State:NY

ZIP:11901

Country:US

Info Phon

e Num:516-727-8600

Emergency Phone Num:516-727-8600

Preparer's Name:MARC LAMENSDORF

CAGE:KO155

=== Contractor Identification ===

Company Name:TRUETECH INC

Address:680 ELTON AVE

Box:City:RIVERHEAD

State:NY

ZIP:11901-2555

Country:US

Phone:516-727-8600

CAGE:06421

Company Name:TRUETECH INC (FORMERLY CHEMICAL COMPOUNDING CORP)

Address:680 ELTON AVE

City:RIVERHEAD

State:NY

ZIP:11901-2555

Country:US

Phone:516-727-8600

CAGE:KO155

===== Composition/Information on Ingredients =====

Ing

red Name:CASTER WAX
Fraction by Wt: 22.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:CARNAUBA WAX
Fraction by Wt: 3.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:MINERAL OIL
CAS:8012-95-1
RTECS #:PY8030000
Fraction by Wt: 26%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3 (MIST); 9596

Ingred Name:LANOLIN
Fraction by Wt: 10.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 6.9%
Other REC
Limits:NONE RECOMMENDED
OSHA PEL:20 MPPCF Z-3
ACGIH TLV:2 MG/M3 RDUST; 9596

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 11.9%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:PIGMENT, BLACK
Fraction by Wt: 1.5%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:15 MG/CUM (AS FE)

Ingred Name:IRON OXIDE
CAS:1309-37-1
RTECS #:NO7400000
Fraction by Wt: 10.2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3 (FE)
ACGI

H TLV:5MG(FE)/M3FUME,B2;96

Ingred Name:CHROMIUM(III) OXIDE CR2O3

CAS:1308-38-9

RTECS #:GB6475000

Fraction by Wt: 8.5%

Other REC Limits:1.0 MG/M3

ACGIH TLV:0.5 MG/M3 TWA AS CR

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:NONE

Effects of Overexposure:NONE.

=====
First Aid Measures
=====

First Aid:NONE.

=====
Fire Fighting Measures
=====

Flash Point:NONE

Extinguish

ing Media:FOAM OR POWDER.

Fire Fighting Procedures:NONE.

Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:NORMAL CLEAN-UP PROCEDURES.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AT AMBIENT TEMPS. WILL MELT IF HEATED.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE

Ventilation:NONE

Protective Gloves:

NONE

Eye Protection:GOGGLES.

Other Protective Equipment:NONE

Work Hygienic Practices:WASH FACE AND HANDS THOROUGHLY AFTER USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:185F/85C

Solubility in Water:INSOLUBLE

Appearance and Odor:ODORLESS PAINT,STICK FORM

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE.

Stability Condition to Avoid:HIG

H TEMPS.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:IAW FED,STATE & LOCAL REGS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person uti

lizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.