View NSN Online: https://aerobasegroup.de/nsn/8010-00-161-7425

PRATT & LAMBERT - WICHITA DIVISION -- 725-402 -- 8010-00-161-7425

Product ID:725-402 MSDS Date:01/01/1985 FSC:8010 NIIN:00-161-7425 MSDS Number: BDDPD === Responsible Party === Company Name: PRATT & LAMBERT - WICHITA DIVISION Emergency Phone Num:316-733-1361 CAGE:PRATT === Contractor Identification === **Company Name: PRATT & LAMBERT** Address:250 PETTIT AVE Box:2153 С ity:BELLMORE State:NY ZIP:11710 Country:US Phone:800-647-2253 CAGE:PRATT Company Name: PRATT AND LAMBERT INC Address:945 BURLINGTON Box:206 City:KANSAS CITY State:MO ZIP:64141 Country:US CAGE:92216 

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: 35.0% OSHA PEL:100 PPM

Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #:OF7525000 Fraction by Wt: O.11% OSHA PEL:0.05 MG/M3;1910.10 25 ACGIH TLV:0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:ZINC CHROMATE Fraction by Wt: < 5%

Ingred Name:TRIETHYLAMINE (SARA III) CAS:121-44-8 RTECS #:YE0175000 Fraction by Wt: 0.4% OSHA PEL:25 PPM/15 STEL ACGIH TLV:10 PPM/15 STEL; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Effects of Overexposure:INHALED-ANESTHETIC, IRITATE AIRWAY; SKIN/EYE IRRITATION HEADACHE, DIZZINESS, COMA,CONFUSION

====

First Aid:INCASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A PHYSICIAN IF SYMPTONS PERSIST. PERFORM ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED.

Flash Point:104 F, 40 C TCC
Lower Limits:1.1
Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL; POLYMER
FO
AM-LARGE FIRE
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE
FOR FIREMEN
Unusual Fire/Explosion Hazard:PRESSURE BUILD-UP FROM EXTREME HEAT MAY
CAUSE EXPLOSION. USE WATER TO COOL CANS. FOR FIRE:FOGNOZZLES

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, & ELECTRICAL, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASSONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD BE GROUNDED WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME CUT,BRAZE, OR WELD COATED MATERIAL WITHOUT VENTILATION.

\_\_\_\_\_

= Exposure Controls/Personal Protection =========

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/ PROPER FILTER OR HOOD Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY& WELDING Protective Gloves:ALOT OF CONTACT Eye Protection:USE EYEWEARIF SPLASHING Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING. Supplemental Safety and Health

BOILING RANGE 155-189 C.

\_\_\_

HCC:F4 Boiling Pt:B.P. Text:311-373 F Evaporation Rate & amp; Reference:< ETHER Percent Volatiles by Volume:59.0

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:FIRES, HEAT, & HOT SURFACES, SPARKS, ELECTRICAL EQUIPMENT

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. INCINERATE IN AP

## PROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the s uitability of this information to their particular situation.