

CORONADO PAINT CO INC -- 67-10 SUP CLEAR VARNISH/SEALER -- 8010-00-165-4420

=====
Product Identification
=====

Product ID:67-10 SUP CLEAR VARNISH/SEALER

MSDS Date:03/29/1991

FSC:8010

NIIN:00-165-4420

MSDS Number: BDDTP

=== Responsible Party ===

Company Name:CORONADO PAINT CO INC

Address:308 OLD COUNTRY RD

City:EDGEWATER

State:FL

ZIP:32032-1812

Country:US

Info Phone Num:904-428-6461

Emergency Phon

e Num:904-428-6461

CAGE:33200

=== Contractor Identification ===

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====
Composition/Information on Ingredients
=====

Ingred Name:MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES
MINERAL SPIRITS *92/2*

CAS:64742-88-7

Fraction by Wt: 35-50%

Other REC Limits:100 PPM

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:

WEIGHT PER GALLON IN POUNDS: 7.5

RTECS #:9999999WG

Ingred Name:VOL ORGANIC CMPD: 3.588

RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION, REDNESS, TEARING & BLURRED VISION. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING & DIARRHEA. ASPIRTION OF MATERIAL INTO THE LUNGS CAN CAUSE

PNEUMONITIS WHICH CAN BE FATAL. INHALATION: CNS DEPRESSION, MUCOUS MEMBRANE, NOSE & THROAT IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: IRRIATION, REDNESS, TEARING & BLURRED VISION. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING & DIARRHEA. ASPIRATION INTO THE LUNGS CAN CAUSE PNEUMONITIS WHICH CAN BE FATAL. INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

=====
===== First Aid Measures =====

First

Aid:EYES/SKIN: FLUSH W/LUKE WARM WATER FOR 15 MINS. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING IF REQUIRED. INGESTION: RINSE MOUTH IMMEDIATELY. GIVE 6-8 OZ OF LIQUID. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:105F

Lower Limits:1%

Upper Limits:6%

Extinguishing Media:CO2, DRY CHEMICAL OR FOAM

Fi

re Fighting Procedures:USE SCBA W/FULL FACEPLATE OPERATED IN PRESSURE DEMAND/POSITIVE PRESSURE MODE. USE WATER TO COOL HEAT EXPOSED CONTAINERS TO PREVENT VAPOR PRESSURE BUILD UP.

Unusual Fire/Explosion Hazard:VAPORS ARE >AIR & MAY TRAVEL ALONG THE GROUND TO AN IGNITION SOURCE & FLASH BACK. CONTAINERS EXPOSED TO HEAT OR FLAME MAY EXPLODE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SMALL: ABSORB ON ABSORBENT MATERIAL. LARGE:

E

LIMINATE IGNITION SOURCES/PREVENT RUNOFF TO SEWERS/STREAMS/BODIES OF WATER/STOP AT SOURCE/DIKE AREA TO PREVENT SPREADING/PUMP LIQUID TO SALVAGE TANK/TAKE U P REMAINDER W/SAND/CLAY/EARTH/SHOVEL INTO DRUMS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS CAN CONTAIN HAZARDOUS PRODUCT RESIDUES EVEN WHEN EMPTY. KEEP CONTAINERS TIGHTLY CLOSED. KEEP AWAY FROM HEAT/ELECT EQUIP/SPARKS/OPEN FLAME.

Other Precautions:KEEP WELDING OR CUTTING EQUIPMENT AWAY FROM PRODUCT. AVOID CONTACT W/EYES, SKIN & BREATHING OF VAPORS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF >TLV, USE A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR. ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLIMENTED TO REDUCE EXPOSURE.

Ventilation:AS REQUIRED TO KEEP AIR Evaporation Rate & Reference:SLOWER THAN BU AC Solubility in Water:NEGLIGIBLE Percent Volatiles by Volume:56 .57%

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avoid:EXCESSIVE HEAT, SPARK, OPEN FLAMES OR OTHER SOURCES OF IGNITION Hazardous Decomposition Products:CO2, CO, VARIOUS HYDROCARBONS

=====
===== Disposal Considerations =====

Waste Disposal Methods:SMALL: ALLOW VOLATILE PORTION TO EVAPORATE IN HOOD. ALLOW SUFFICIENT TIME FOR VAPORS TO COMPLETELY CLEAR HOOD DUCTWORK. LARGE: INCINERATE. DISPOSE CONTAMINATED ABSORBENT IN LANDFILL. DISPOSE OF ALL SPILLS IN ACCORDANCE W/LOCAL/STATE/FEDERAL REGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this doc

ument should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.