

CARROLL/LTD INC -- ASTM D600 -- 8010-00-165-4782

=====  
Product Identification  
=====

Product ID:ASTM D600  
MSDS Date:01/01/1985  
FSC:8010  
NIIN:00-165-4782  
MSDS Number: BDDVF  
=== Responsible Party ===  
Company Name:CARROLL/LTD INC  
Address:2656 SALMON ST  
City:PHILADELPHIA  
State:PA  
ZIP:19125-4034  
Country:US  
CAGE:59973  
=== Contractor Identification ===  
Company Name:CARROLL/LTD INC  
Address:2656 SALMON ST  
Box:City:PHILADELPHIA  
State:PA  
ZIP:19125-4034  
Country:US  
CAGE:59973

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION\_INGREDIENT

=====  
Hazards Identification  
=====

Effects of Overexposure:INHALATION-HEADACHE, UNCOORDINATION. SKIN IRRITANT. INGESTION-VOMITING DEPRESSION

=====  
First Aid Measures  
=====

First Aid:REMOVE TO FRESH AIR. ARTIFICIAL RESPIRATI  
ON OR OXYGEN. IF  
SWALLOWED DO NOT INDUCE VOMITING. ASPIRATION MAY LEAD TO PULMONARY  
EDEMA AND PNEUMONIA. SKIN CONTACT-WASH WITH SOAP AND WATER. CALL  
DOCTOR.

=====  
Fire Fighting Measures  
=====

Flash Point:105F, 40.6 TCC  
Lower Limits:1.1  
Upper Limits:6.0  
Extinguishing Media:WATER SPRAY FOAM C02 ORX CHEMICAL  
Fire Fighting Procedures:USE WATER SPRAY OR FOG AVOID SPREADING BY  
FLOODING  
Unusual Fire/Explosion Hazard:NONE

=====  
Accidenta

I Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION. COVER WITH INERT ABSORBENT MATERIAL AND REMOVE TO DISPOSAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:LABEL: CAUTION! COMBUSTIBLE KEEP AWAY FROM HEAT AND OPEN FLAME

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF CONCENTRAION EXCEEDS TLV USE BUREAU OF MINES APPROVED RESPIRATO

R  
Ventilation:LOCAL EXHAUST  
Protective Gloves:YES  
Eye Protection:GOGGLES  
Other Protective Equipment:NOT REQUIRED  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:380F L93.3C  
Vapor Pres:2.5  
Vapor Density:3.9  
Spec Gravity:0.95  
Evaporation Rate & Reference:LBUTYL ACETATE  
Solubility in Water:SLIGHT  
Appearance and Odor:BLUE-VIOLET LIQUID, MINERAL SPIRITS ODOR  
Percent Volatiles by Volume:38

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
ORGANIC PEROXIDES  
Stability Condition to Avoid:KEEP AWAY FROM HEAT AND OPEN FLAME  
Hazardous Decomposition Products:CARBON MONOXIDE COBALT FUMES

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN SUITABLE FURNACE OR BURY IN APPROVED LANDFILL

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use

by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.