

EASTMAN KODAK CO. -- 199 7915,VERSAMAT 885 DEVELOPER STATER -- 6750-00-165-7189  
===== Product Identification =====

Product ID:199 7915,VERSAMAT 885 DEVELOPER STATER

MSDS Date:05/23/1985

FSC:6750

NIIN:00-165-7189

MSDS Number: BDDXN

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phon

e Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000

Fraction by Wt: 1-5%

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Na

me:SODIUM BROMIDE  
CAS:7647-15-6  
RTECS #:VZ3150000  
Fraction by Wt: 30-40%  
Other REC Limits:NONE ESTABLISHED  
OSHA PEL:NONE ESTABLISHED  
ACGIH TLV:NONE ESTABLISHED

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 60-70%  
Other REC Limits:NONE ESTABLISHED

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Effects of Overexposure:EYES,SKIN,MUCOUS MEMBRANES:L  
OW HAZARD,PER MFG.  
PRUDENCE REGARDING CHEMICAL IS SUGGESTED.

=====  
First Aid Measures  
=====

First Aid:EYES,SKIN,MUCOUS MEMBRANES:FLUSH W LG AMTS H\*2O AT LEAST 15  
MIN; INHALE:REMOVE TO FRESH AIR,KEP CALM;INGEST:RISE MOUTH,DRINK  
EXCESS WATER,DO NOT INDUCE VOMIT.GET IMMEDIATE MEDICAL ATTENTION  
FOR EYES,INGEST,INHALE, OR SKIN BURNS(MFG:NONE INDICATED)

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Extinguishing Media:USE AGENT APPROPRIATE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP;WATER SPRAY COOL  
CONTAINERS.  
Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE IN HEAT OF  
FIRE.ACID SOLUTION;AVOID PHYSICAL CONTACT.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:DO NOT TOUCH SPILLED MATERIAL. WEAR PROTECTIVE  
EQUIPMENT.STOP LEAK IF POSSIBLE WITHOUT RISK. SM SP:ABSORB W  
COMMERCIAL ABSORBENT & PUT IN APPR

CONTAINERS. LG SP: CONTAIN W  
DIKE & TRANSFER TO APPR CONTAINERS (SOLUTION IS ACID).

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED  
AREA; PROTECT FROM PHYSICAL DAMAGE & AVOID CONTACT WITH SKIN (ACID  
SOLUTION). AVOID CONTACT WITH ALKALIES.

Other Precautions:REMOVE & WASH CONTAMINATED CLOTHING. MAINTAIN STRICT  
HYGIENE. MFG INDICATED PRODUCT OF LOW HAZARD, CONTRADICTING PH  
INFO, AND THAT NO PRO  
TECTIVE EQUIPMENT OR SPECIAL PRECAUTIONS  
NEEDED.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:FOR VAPOR EXPOSURE, USE APPR ORGANIC VAPOR  
RESPIRATOR.

Ventilation:ADEQUATE TO ELIMINATE FUMES:MECHANICAL (GEN/LOCAL EXHAUST)

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL WORK CLOTHING;FACE SHIELD WHEN USING  
PRODUCT.

Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:C3

Boiling Pt:B.P. Text:>212F, >100C

Vapor Pres:32

Vapor Density:0.6

Spec Gravity:1.35

pH: