View NSN Online: https://aerobasegroup.de/nsn/5315-00-165-8470

DAVLIN PAINT CO. -- WHITE INDOOR PRIMER, SEALER BTTS179 -- 8010-00-165-8470

======== Product Identification ============

Product ID:WHITE INDOOR PRIMER, SEALER BTTS179

MSDS Date:04/26/1988

FSC:8010

NIIN:00-165-8470

MSDS Number: BDDXW === Responsible Party ===

Company Name: DAVLIN PAINT CO.

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA ZIP:94702 Country:US

Preparer's Name: PATRICIA SHAW

CAGE:DO185

==

= Contractor Identification ===

Company Name: DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA ZIP:94702 Country:US

Phone:510-848-2863

CAGE:3Z268

Company Name: DAVLIN PAINT CO.

Address:P.O. BOX 2308

Box:2308

City:BERKELEY

State:CA ZIP:94702

Phone:415-889-7098

CAGE:DO185

====== Composition/Information on Ingredients ========

Ingred Name: VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4 RTECS #:Ol6180000 Fraction by Wt: 30%

Other REC Limits:125 PPM OSHA PEL:300 PPM/400

STEL

ACGIH TLV:300 PPM; 9192

Ingred Name: TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000 Fraction by Wt: 10% Other REC Limits:DUST OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

========= Hazards Identification ============================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: MANY PETROLEUM HYDROCARBONS AND

SYNTHETIC LUBRICANTS POSE POTENTIAL HUMAN HEALTH

RISKS. AS A

PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS OR FUMES SHOULD BE MINIMIZED. CHRONIC EXPOSURE MAY CAUSE DAM AGE TO CENTRAL NERVOUS SYSTEM, RESPIRATORY SYSTEM, LUNGS, EYES, SKIN, GASTROINTESTINAL TRACT, LIVER, SPLEEN & KIDNEYS.

Explanation of Carcinogenicity: CHEMICALS MAY CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

- Effects of Overexposure:INHAL-VAPORS CAN CAUSE NASAL & RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA & HEADACHE. SKIN
- -CAN CAUSE MODERATE IRRITATION, DEFATTING & DERMATITIS. EYE-SEVERE IRRITATION, TEARING, REDN ESS & BLURRED VISION. INGEST-CAN CAUSE IRRITATION OF THE DIGESTIVE TRACT AND SIGNS OF CENTRAL NERVOUS SYS DEPRESSION. *
- Medical Cond Aggravated by Exposure:RESPIRATORY TRACT IRRITATION, DERMATITIS, NAUSEA. *CAN ENTER LUNGS DURING SWALLOWING OR VOMITING AND CAUSE LUNG INFLAMMATION.

First Aid:EYES-FLUSH W/WATER FOR 1

5 MINUTES, SKIN-REMOVE CONTAMINATED

CLOTHING, WASH THOROUGHLY W/SOAP AND WATER. INHAL-REMOVE VICTIM TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION OR ADMINISTER OXYGEN IF NEEDED. I NGEST-GIVE WATER OR MILK TO DRINK & PHONE FOR MEDICAL ATTENTION. DO NOT INDUCE VOMITING UNLESS DIRECTED BY MEDICAL PERSONNEL. IF MEDICAL ADVICE NOT AVAILABLE TAKE PERSON TO NEAREST EMERGENCY HOSPITAL.

Flash Point Method:SCC

Flas

h Point:105F/41C Lower Limits:1.0% Upper Limits:6.1%

Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures: USE EXTINGUISHERS DESIGNED TO EXTINGUISH NFPA FLAMMABLE LIQUID FIRE. APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING PERSONNEL. WATER MAY BE INEFFECTIVE.

Unusual Fire/Explosion Hazard: VAPORS FORM AN EXPLOSIVE MIXTURE WITH AIR BETWEEN LOWER AND UPPER EXPLOSIVE LIMITS WHICH CAN BE IGNITED. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EX/HEAT.

=====		
	Accidental Release Measures	

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL IGNITION SOURCES. VENTILATE AREA. EQUIP EMPLOYEES WITH APPROPRIATE EQUIPMENT. DIKE AROUND SPILLED AREA. COVER SPILL WITH INERT ABSORBANT AND TRANSFER U SING NON-SPARKING TOOLS.

========== Handling and Storage ============

Handling and Storage Precautions:STORE BELOW 80 DEG F IN CLOSED CONTAINER. STORE IN ORIGINAL CONTAIN

ER. AVOID FLAME AND HIGH

TEMPERATURE. DO NOT STORE NEAR OXIDIZING AGENTS OR ACIDS.
Other Precautions:DO NOT TAKE INTERNALLY, AVOID PROLONGED INHALATION.
GROUND ALL CONNECTIONS, CONTAINERS, ETC, WHEN POURING OR
TRANSFERRING TO MINIMIZE STATIC ELECTRICITY. USE NON-SPARKING
TOOLS.

===== Exposure Controls/Personal Protection ========

Respiratory Protection:WHEN SPRAYING THIS MATERIAL USE A NIOSH APPROVED CARTRIDGE RESPIRATOR OR GAS MASK TO KEEP AIRBORNE MISTS AND VAPOR

CONCENTRATIONS BELOW TLV. IN POORLY VENTILATED AND CONFINED SPACES, USE A FRESH-AIR S UPPLY OR SELF CONTAINED BREATH/APPARATUS

Ventilation: GENERAL MECHANICAL VENTILATION OR LOCAL EXHAUST SHOULD BE ADEQUATE TO KEEP VAPOR CONCENTRATIONS BELOW TLV. *

Protective Gloves:IMPERVIOUS TO PREVENT SKIN CONTACT.

Eye Protection: CHEMICAL SAFETY GLASSES OR GOGGLES

Other Protective Equipment: USE IMPERMEABLE APRONS AND PROTECTIVE CLOTHING TO PREVENT EXPOSURE TO SKIN. HEADCAPS ARE RECOMMEND

ED.
Work Hygienic Practices:AFTER USING, WASH BEFORE EATING, TOILETING OR

Supplemental Safety and Health

* VENTILATION EQUIPMENT MUST BE EXPLOSION PROOF.

======== Physical/Chemical Properties ===========

Boiling Pt:B.P. Text:306F Vapor Density:>AIR Spec Gravity:1.3

SMOKING.

Evaporation Rate & Deference: SLOWER THAN ETHER

Solubility in Water: NOT WATER/SOLUBLE

Appearance and Odor:PIGMENTED LIQUID. MILD SOLVENT ODOR.

========== Stability and Reactivity Data ===

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:DO NOT EXPOSE TO HEAT OR IGNITION SOURCES.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON DIOXIDE AND/OR MONOXIDE, LOW MOLEULAR WEIGHT HYDROCARBONS AND ORGANIC ACIDS.

======= Disposal Considerations ===========

Waste Disposal Methods:KEEPT OUT DRAINS, SEWERS AND WATERWAYS. DISPOSE IN ACCORDANCE WITH LOCAL, COUNTY, STATE AN D FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.