

3M COMPANY -- SCOTCHGRIP CONTACT CEMENT, 2218 -- 8040-00-165-8614

=====  
Product Identification  
=====

Product ID:SCOTCHGRIP CONTACT CEMENT, 2218

MSDS Date:01/01/1985

FSC:8040

NIIN:00-165-8614

MSDS Number: BDDZC

=== Responsible Party ===

Company Name:3M COMPANY

Address:3M CTR 224-2S-25

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1341

Emergency Phone Num:612-733-1341

CAGE

:76381

=== Contractor Identification ===

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATE (MAY CONTAIN 0.4-0.8%  
BENZENE)

Fraction by Wt: 40%

ACGIH TLV:200 PPM (MFR)

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 25%

OSHA PEL:1000PPM  
ACGIH TLV:750PPM/1000STEL;9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingrid Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 1  
Spec Gravity:0.79  
Evaporation Rate & Reference:2 (ETHER= 1)  
Solubility in Water:VERY SLIGHT  
Appearance and Odor:THIN GREEN LIQUID  
Percent Volatiles by Volume:75

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations ==

=====

Waste Disposal Methods:MFR RECOMMENDS INCINERATION. WASTE DISPOSAL METHOD MUST BE IAW FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.