

AMERON INDUSTRIAL COATINGS DIVISION -- 787-609, GRAY 36118 -- 8010-00-166-3160

=====  
Product Identification  
=====

Product ID:787-609, GRAY 36118

MSDS Date:01/01/1985

FSC:8010

NIIN:00-166-3160

MSDS Number: BDFCK

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Info Phone Num:714-529-4597

Emergency Phone N

um:714-529-4597

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 16.3%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (

SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 8.6%  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)  
CAS:78-83-1  
RTECS #:NP9625000  
Fraction by Wt: 3.5%  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPANOL  
RTECS #:NP8050000  
Fraction by Wt: 7.1%  
ACGIH TLV:400PPM

Ingred Name:ISOBUTYL ACETATE (SARA III)  
CAS:110-19-0  
RTECS #:AI4025000  
Fraction  
by Wt: 19.3%  
OSHA PEL:150 PPM  
ACGIH TLV:150 PPM; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

=====  
===== Hazards Identification =====

Effects of Overexposure:INHALATION: ANESTHETIC. IRRITATION OF  
RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

=====  
===== First Aid Measures =====

First Aid:IN CASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER  
SHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH

AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.

=====  
===== Fire Fighting Measures =====

Flash Point:40F, T.C.C.

Lower Limits:1.3

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL; POLYMER FOAM FOR  
LARGE FIRES

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS SHOULD BE  
AVAILABLE

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE DUE TO PRESSURE BUILD-UP

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
BREATHING VAPORS. VENTILATE AREA. REMOVE WITH ERT ABSORBENT AND  
NON-SPARKING TOOLS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE  
QUANTITIES IN BUILDINGS AND PROTECTED FOR STORAGE OF NFPALASS ONE  
FLAMMABLE LIQUIDS.

Other Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED  
WHEN POURING. AVOID FREE FALL OF LIQ

UID IN EXCESS OF A FEW INCHES.

DO T FLAME CUT, WELD OR BRAZE DRY COATING W/OUT RESPIRATOR.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:MECHANICAL FILTER OR CHEMICAL-MECHANICAL FILTER  
TYPE RESPIRATOR

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST

Protective Gloves:REQUIRED

Eye Protection:SPLASH-PROOF GOGGLES

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO  
CONTAMINATED CLOTHING.

Supplemental Safety and Health

P.O. BOX 2153/ W

ICHITA, KANSAS 67201.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-287F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:73

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES, HEAT AND HOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Method

s:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND  
FEDEERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document  
should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.