

SHELL OIL COMPANY -- AEROSHELL OIL W 120 -- 9150-00-168-6889

=====
Product Identification
=====

Product ID:AEROSHELL OIL W 120

MSDS Date:01/01/1987

FSC:9150

NIIN:00-168-6889

MSDS Number: BDFFK

=== Responsible Party ===

Company Name:SHELL OIL COMPANY

Emergency Phone Num:713 473 9461

CAGE:54527

=== Contractor Identification ===

Company Name:SHELL OIL COMPANY

Box:2463

City:HOUSTON

State:TX

ZIP:77210

Country:US

Phone:800-231-6950

CAGE:54527

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM HYDROCARBONS

Fraction by Wt: 96.5%

ACGIH TLV:>5GM/KG

Ingred Name:POLYMETHACRYLATE

Fraction by Wt: 3.0%

Ingred Name:PHENOL,ANTIOXIDANT,HINDERED

Fraction by Wt: 0.5%

=====
Hazards Identification
=====

Effects of Overexposure:EXP TO VAPORS/MIST-POSS PULMONARY
IRRIT,DIZZ,NAUSEA. REPEATED CONTACT-DERMATITIS,OIL ACNE

=====

===== First Aid Measures =====

First Aid:EYES-FLUSH W/WATER,GET MEDI ATTN. SKIN-WASH W/SOAP & WATER.LAUNDRER CLOTHES BEFORE REUSE. INHAL-GET TO FRESH AIR & MED ATTN. INGEST-DO NOT INDUCE VOMIT. GET MED ADVICE.

===== Fire Fighting Measures =====

Flash Point:440F/227C/PMCC
Extinguishing Media:WATER FOG,FOAM,DRY CHEMICAL OR CARBON DIOXIDE
Fire Fighting Procedures:USE PROPER PROTECT EQUIP,INCL NIOSH APPRD
SLF-CNTD BR APPARA

Unusual Fire/Explosion Hazard:NONE UNUSUAL. WATER CAN COOL FIRE-EXPOSED CONTAINERS.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR RESPIRATOR & PROTECT CLOTH. SHUT OFF SOURCES IF LEAK IF POSS. DIKE & CONTAIN. REMOVE W/VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSEL. SOAK UP RESIDUE W/ABSORBENT LIKE CLAY OR SAND. FLUSH AREA W /WATER

===== Handling and Storage =====

Handling and Storage Precautions:MINIMIZE SKIN CONTACT. WASH W/SOAP & WATER BEFORE EATING,DRINKING OR USING TOILET FACILITIES. LAUNDRER CONTAM CLOTH BEFORE REUSE.
Other Precautions:SPILLS ENTERING WATER COURSES OR SURFACE WATERS MUST BE REPORTED TO THE NATIONAL RESPONSE CTR,800-424-8802

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH-APPRD RESPIR TO PREVENT OVER-EXPOS.
Protective Gloves:RUBBER
Eye Protection:GOGGLES/SAFETY GLASSES
Other Protective Equipment:AS
REQD TO MINIMIZE SKIN CONTACT.
Supplemental Safety and Health
MIL-L-22851,TYPE II

===== Physical/Chemical Properties =====

HCC:V6
Spec Gravity:0.88
Solubility in Water:INSOLUBLE
Appearance and Odor:DARK AMBER OIL,SLIGHT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:HEAT,OPEN FLAMES, OXIDIZING MATLS & MIST FORMATION
Hazardous Decomposition Products:CARBON MONOXI

DE & UNIDENTIFIED ORG
CMPD DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: PLACE IN APPROPRIATE DISPOSAL FACIL IAW LOCAL
REGS. KEEP OUT OF SURFACE WATERS & ANY WATER COURSES OR SEWERS
ENTERING OR LEADING TO SURFACE WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner wh
atsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.