View NSN Online: https://aerobasegroup.com/nsn/9130-00-180-6385 ASHLAND OIL CO. -- JP-7 -- 9130-00-180-6385 Product ID:JP-7 MSDS Date:01/01/1985 FSC:9130 NIIN:00-180-6385 MSDS Number: BDGDX === Responsible Party === Company Name: ASHLAND OIL CO. Address:1409 WINCHESTER AVE Box:391 City: ASHLAND State:KY ZIP:41114 Country:US CAGE:81355 === Contractor Identification === Company Name: ASHLAND INC Address:1409 WINCHESTER AVE Box:39 1 City: ASHLAND State:KY ZIP:41114 Country:US Phone:800-622-6846 CAGE:81355 ======= Composition/Information on Ingredients ======== Ingred Name: ALIPHATIC HYDROCARBON Fraction by Wt: 60.0% ACGIH TLV:5000PPM. Ingred Name: AROMATIC HYDROCARBON Fraction by Wt: 3.0% ACGIH TLV:100PPM. =========== Hazards Identification ========================== Effects of Overexposure: EYES: MODERATE IRRIT. SKIN: SLIGHT IRRIT., DEFATTING. INHAL: NASAL, RESP. IRRIT., FATIGUE. SEE SUPP. DATA

======== First Aid Measures =================================
First Aid:SKIN: WASH W/SOAP & WATER.REMOVE CLOTHING. WASH BEFORE REUSE.EYES:FLUSH W/WATER, CALL DR. INGEST:GIVE 2 GLASSES OF WATER; INDUCE VOMIT. CALL DR. NOTHG BY MOUTH TO AN UNC. PERSON.INHAL:MOVE TO FRESH AI R. GIVE O*2.KEEP WARM,QUIET.
=========== Fire Fighting Measures ============
Flash Point:140F Lower Limits:0.90 Extinguishing Media:DRY CHEMICAL,CO*2,ALCOHOL Fire Fighting Procedures:SELF-CONTAI NED BREATHING APPARATUS W/FULL FACEPIECE(POS.PRES Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM(EVEN EMPTY) BECAUSE PRODUCT CAN IGNITE.FLASH BACK
======== Accidental Release Measures ==========
Spill Release Procedures:SMALL SPILL:ABSORB LIQUID ON PAPER,VERMICULITE,FLOOR ABSORBENT, OR OTHER ABSORBENT MATL & TRANSFER TO HOOD.LARGE SPILL:ELIMINATE ALL IGNITION SOURCES.PERSONS NOT WEARING PROT.EQUIP. SHOULD BE EXCLUDED FRO M AREA.REMAINING LIQ.TAKEN. BY SAND,CLAY
======================================
Handling and Storage Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED.SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES(VAPOR,LIQUID,&/OR SOLID.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NIOSH/MESA JOINTLY APPD SELF-CONTAINED BREATHG APPARATUS W/FACEPC.  Ventilation:PROVIDE SUFFICIENT MECHANICAL(GENERA L &/OR LOCAL EXHAUST.  Protective Gloves:NEOPRENE Eye Protection:CHEM.SPLASH GOGGLES  Other Protective Equipment:WEAR IMPERVOIUS CLOTHING & BOOTS.  Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:F4 Boiling Pt:B.P. Text:360F Vapor Pres:0.5 Vapor Density:5.48 Spec Gravity:0.79 Evaporation Rate & Description Rate & Desc

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS, STRONG ALKALIES, & STRONG MINERAL ACIDS.

Stability and Reactivity Data ============

OXIDIZING AGENTS,STRONG ALKALIES, & STRONG MINERAL ACIDS. Hazardous Decomposition Products:CO\*2,CO,VARIOUS HYDROCARBONS,ETC;

======= Disposal Considerations ============

Waste Disposal Methods:SMALL SPILL:ALLOW VOLATILE PORTION TO EVAPORATE IN HOOD,ALLOW SUFFICIENT TIME FOR VAPORS TO COMPLETELY CLEAR HOOD DUCT WORK.DESTROY REMAIN. MATL BY BURNING IN IRON PAN. LARGE

SPILL:DESTROY BY INCINERA TION. MATL COLLECTED ON ABSORB. PLACE LANDFL

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume respons ibility for the suitability of this information to their particular situation.