

3M -- 3M SUPER 74 FOAMFAST ADHESIVE -- 8040-00-181-7761

===== Product Identification =====

Product ID:3M SUPER 74 FOAMFAST ADHESIVE

MSDS Date:01/01/1987

FSC:8040

NIIN:00-181-7761

MSDS Number: BDGMM

=== Responsible Party ===

Company Name:3M

Emergency Phone Num:612 733 1110

CAGE:0F0U5

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:PACEBROOK LTD

Address:15 GOSDITCH ST

City:CIRENCESTER GLOS GL7 2AG

Country:UK

Phone:NONE

CAGE:0F0U5

===== Composition/Information on Ingredients =====

Ingred Name:PENTANE

CAS:109-66-0

RTECS #:RZ9450000

Fraction by Wt: -23%

OSHA PEL:1000 PPM/750 STEL

ACGIH TLV:600 PPM/750STEL;9293

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt:

-12%  
OSHA PEL:1000PPM  
ACGIH TLV:750PPM/1000STEL;9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPARAFIN SOLVENT(HYDROCARBONS) \*MFG'S SUGGESTED TLV  
Fraction by Wt: -3%  
ACGIH TLV:300PPM\*

Ingred Name:DIMETHYLETHER (PROPELLANT)  
RTECS #:IY5500000  
Fraction by Wt: -40%

=====  
===== Hazards Identification =====

Effects of Overexposure:INHAL:CONCENT.VAPS MAY PROD. ANESTHETIC  
EFFCTS.EYE CONTCT-DIRECT-MILD IRRIT.INGEST-GASTROINTESTIN(SU

=====  
===== First Aid Measures =====

First Aid:EYE CONTCT-IMMED. FLUSH EYES W/PLENTY OF WATER F/AT LEAST 10  
MINUTES & CALL A PHYSICIAN. SKIN CONTCT-WASH W/SOAP & WATER.  
INHALATION-PROVIDE FRESH AIR.

=====  
===== Fire Fighting Measures =====

Flash Point:-50 F PROPEL-46  
Lower Limits:1  
Upper Limits:19.0  
Extinguishing Media:CO\*2, FOAM, DRY CHEM  
Fire Fighting Procedures:TREAT AS FLAMMABLE PRESSURIZED CONTNR.  
Unusual Fire/Explosion Hazard:PRESSURIZED  
CONTAINER.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL IGNIT SOURCES & VENT SPILL AREA  
TO DISSIPATE FUMES.COLLECT SPILLED MATERIAL.PLACE IN A U.S. DOT  
APPRVD CONTAINER & SEAL.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOV 120 F. KEEP AWAY FRM  
HEAT, SPARKS,OPN FLAME. USE ONLY IN WELL VENT. AREA W/ADEQ. AIR  
MOVEMENT TO REMOV VAPS & VAP BUILDUP

Other Precautions:KEEP OUT OR REACH OF CHILDREN. AVOID PROLNG BREATHING OF VAPORS. AVOID EYE CONTACT. AVOID SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AS REQD.

Ventilation:YES-LOC. EXHAUST-PREFERRED, MECH-FOR LOW USAGE.

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

HAZ. INGRED:STYRENE/BUTADIENE ELASTOMER, TERPENE RESIN, CHLORINATED PARRAFIN, WOOD ROSIN, DYE & ANTIOXIDANT. EFF. OR OVREXPOSR:IRRITATION NAUSEA

& VOMITING.PROC. UNDER:3M SUPER 74 FOAMFAST ADHESIV

===== Physical/Chemical Properties =====

HCC:V3

Vapor Density:>2

Spec Gravity: