

AKZO COATINGS INC -- TL 102 (MIL-T-81772A) -- 8010-00-181-8079

=====  
Product Identification  
=====

Product ID:TL 102 (MIL-T-81772A)

MSDS Date:11/01/1985

FSC:8010

NIIN:00-181-8079

MSDS Number: BDGPC

=== Responsible Party ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

City:ORANGE

State:CA

ZIP:92661

Country:US

Info Phone Num:714-637-1750

Emergency Phone Num:714-637-1750; CHEMTREC 800-424-9300

Preparer's Name:LEE A. DICKINSON

CAGE:98502

=== Contractor Identification ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

Box:City:ORANGE

State:CA

ZIP:92661

Country:US

Phone:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

=====  
Composition/Information on Ingredients  
=====

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

Fraction by Wt: 39-41%

Other REC Limits:N/K

OSHA PEL:S,100 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 29-31%  
Other REC Limits:N/K  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ACETATE (SARA III)  
CAS:123-86-4  
RTECS #:AF7350000  
Fraction by Wt: 9-11%  
Other REC Limits:N/K  
OSHA PEL:150 PPM/200 STEL  
ACGIH TLV:150 PPM/200STEL;9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RT  
ECS #:XS5250000  
Fraction by Wt: 8-12%  
Other REC Limits:N/K  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 6-10%  
Other REC Limits:N/K  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:N/K  
Reports of Carcinogenicity:NT

P:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NIOSH STUDIES INDICATE THAT RELATED GLYCOL ETHERS CAUSED REPRODUCTIVE DISORDERS IN LABORATORY ANIMALS (RAT,MICE) AND MAY HAVE POTENTIAL FOR CAUSING SIMILAR DISORDERS IN HUMANS .

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHAL:IRRIT TO

NOSE,THROAT.EYE:IRRIT.INGEST:HEADACHE,NAUSEA,DIZZINESS.SKIN:HARMFUL IF ABSORBED.MAY CAUSE DERMATITIS.

Medical Cond Aggravated by Exposure:N/K .

=====

First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR.ADMIN OXYGEN.CALL MD.EYES:FLUSH WITH WATER FOR AT LEAST 15 MIN.CALL MD.SKIN:REMOVE CONTAM CLOTHING,WASH WITH WATER FOR AT LEAST 15 MIN.CALL MD.WASH CONTAM CLOTHING BEFORE REU SE.INGEST:CONSULT PHYSICIAN AT ONCE.DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:23F,-5C

Lower Limits:1.0

Upper Limits:N/K

Extinguishing Media

:FOAM,CARBON DIOXIDE,DRY CHEMICALS.USE H\*2O TO COOL SURF&PROTECT PERS ONLY.EXCLUDE AIR.STEAM&/OR WATER SPRAY MAY BE USED.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .USE WATER SPRAY ONLY TO COOL SURFACE & PROTECT PERSONNEL.EXCLUDE AIR.

Unusual Fire/Explosion Hazard:VAPOR FORMS EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER & LOWER EXPLOSION LIMITS.UNOPENED CNTNRS MAY RUPTURE WHEN HOT.CARBON MONOXIDE AND DIOXIDE MAY BE EMITTED.

=====

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCE OF IGNITION.VENTILATE AREA.PREVENT FROM ENTERING SEWERS OR DRAINS.CONTAIN SPILLS WITH SAWDUST OR OTHER ABSORBANT.CLEAN AREA.

Neutralizing Agent:N/K

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE.DO NOT HANDLE OR STORE NEAR FLAMES,HEAT,STRONG OXIDANTS.USE ADEQUATE VENTILATION.

Other Pre

cautions:EMPTY CONTR MAY BE HAZARDOUS.FUMES ARE EXTREMELY  
FLAMMABLE.EQUIP SHOULD BE ELECTRICALLY GROUNDED.DO NOT WELD EMPTY  
CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR  
EXPOSURE OF CONCERN . AIR SUPPLIED.SELF-CONTAINED RESPIRATOR IN  
CONFINED AREA.

Ventilation:ADEQUATE TO KEEP CONCENTRATIONS BELOW TLVS.EXPLOSION PROOF  
VENTILATION EQUIPMENT.

Protective Gloves:CHEMICALLY RE  
SISTANT.

Eye Protection:CHEM WORK GOG,FACESHLD OPTIONAL .

Other Protective Equipment:LONG SLEEVES,PROTECTIVE APRON.EYE BATH &  
SAFETY SHOWER.

Work Hygienic Practices:N/K

Supplemental Safety and Health

N/K

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:176-321F

Melt/Freeze Pt:M.P/F.P Text:N/K

Decomp Temp:Decomp Text:N/K

Vapor Pres:2-70 MMHG

Vapor Density:>1 (AIR=1)

Spec Gravity:0.89 (H\*2O=1)

Evaporation Rate & Reference:>1 (ETHER=1)

S

solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR,SOLVENT ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:STORAGE AT HIGH TEMPERATURE,SPARKS,AND  
OPEN FLAME.

Hazardous Decomposition Products:CARBON MONOXIDE AND DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN A

CCORDANCE WITH

FEDERAL, STATE AND LOCAL REGULATIONS .TREAT AS HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume

responsibility for the suitability of this information to their particular situation.