

AKZO COATINGS INC -- TL 102 (MIL-T-81772A) -- 8010-00-181-8080

=====
Product Identification
=====

Product ID:TL 102 (MIL-T-81772A)

MSDS Date:11/01/1985

FSC:8010

NIIN:00-181-8080

MSDS Number: BDGPH

=== Responsible Party ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

City:ORANGE

State:CA

ZIP:92661

Country:US

Info Phone Num:714-637-1750

Emergency Phone Num:714-637-1750; CHEMTREC 800-424-9300

Preparer's Name:LEE A. DICKINSON

CAGE:98502

=== Contractor Identification ===

Company Name:AKZO COATINGS INC

Address:434 W. MEATS STREET

Box:City:ORANGE

State:CA

ZIP:92661

Country:US

Phone:714-637-1750; CHEMTREC 800-424-9300

CAGE:98502

=====
Composition/Information on Ingredients
=====

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

Fraction by Wt: 39-41%

Other REC Limits:N/K

OSHA PEL:S,100 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 29-31%
Other REC Limits:N/K
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 9-11%
Other REC Limits:N/K
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RT
ECS #:XS5250000
Fraction by Wt: 8-12%
Other REC Limits:N/K
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 6-10%
Other REC Limits:N/K
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

LD50 LC50 Mixture:N/K
Reports of Carcinogenicity:NT

P:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NIOSH STUDIES INDICATE THAT RELATED GLYCOL ETHERS CAUSED REPRODUCTIVE DISORDERS IN LABORATORY ANIMALS (RAT,MICE) AND MAY HAVE POTENTIAL FOR CAUSING SIMILAR DISORDERS IN HUMANS .

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHAL:IRRIT TO

NOSE,THROAT.EYE:IRRIT.INGEST:HEADACHE,NAUSEA,DIZZINESS.SKIN:HARMFUL IF ABSORBED.MAY CAUSE DERMATITIS.

Medical Cond Aggravated by Exposure:N/K

===== F

irst Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR.ADMIN OXYGEN.CALL MD.EYES:FLUSH WITH WATER FOR AT LEAST 15 MIN.CALL MD.SKIN:REMOVE CONTAM CLOTHING,WASH WITH WATER FOR AT LEAST 15 MIN.CALL MD.WASH CONTAM CLOTHING BEFORE REU SE.INGEST:CONSULT PHYSICIAN AT ONCE.DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:23F,-5C

Lower Limits:1.0

Upper Limits:N/K

Extinguishing Media:

FOAM,CARBON DIOXIDE,DRY CHEMICALS.USE H₂O ONLY TO COOL SURF&PROTECT PERS.EXCLUDE AIR. STEAM&/OR H₂O SPRAY MAY BE USED.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .USE WATER SPRAY ONLY TO COOL SURFACE & PROTECT PERSONNEL.EXCLUDE AIR.

Unusual Fire/Explosion Hazard:VAPOR FORMS EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER & LOWER EXPLOSION LIMITS.UNOPENED CNTNRS MAY RUPTURE WHEN HOT.CARBON MONOXIDE AND DIOXIDE MAY BE EMITTED.

=====

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCE OF IGNITION.VENTILATE AREA.PREVENT FROM ENTERING SEWERS OR DRAINS.CONTAIN SPILLS WITH SAWDUST OR OTHER ABSORBENT.CLEAN AREA.

Neutralizing Agent:N/K

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE.DO NOT HANDLE OR STORE NEAR FLAMES,HEAT,STRONG OXIDANTS.USE ADEQUATE VENTILATION.

Other Prec

autions:EMPTY CONTR MAY BE HAZARDOUS.FUMES ARE EXTREMELY
FLAMMABLE.EQUIP SHOULD BE ELECTRICALLY GROUNDED.DO NOT WELD EMPTY
CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR
EXPOSURE OF CONCERN .AIR SUPPLIED.SELF-CONTAINED RESPIRATOR IN
CONFINED AREA.

Ventilation:ADEQUATE TO KEEP CONCENTRATIONS BELOW TLVS.EXPLOSION PROOF
VENTILATION EQUIPMENT.

Protective Gloves:CHEMICALLY RESI
STANT GLOVES.

Eye Protection:CHEM WORK GOG,FACESHLD OPTIONAL

Other Protective Equipment:LONG SLEEVES,PROTECTIVE APRON.EYE BATH &
SAFETY SHOWER.

Work Hygienic Practices:N/K

Supplemental Safety and Health

N/K

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:176-321F

Melt/Freeze Pt:M.P/F.P Text:N/K

Decomp Temp:Decomp Text:N/K

Vapor Pres:2-70 MMHG

Vapor Density:>1 (AIR=1)

Spec Gravity:0.89 (H*2O=1)

Evaporation Rate & Reference:>1 (ETHER=
1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR,SOLVENT ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:STORAGE AT HIGH TEMPERATURE,SPARKS,AND
OPEN FLAME.

Hazardous Decomposition Products:CARBON MONOXIDE AND DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE

IN ACCORDANCE WITH
FEDERAL, STATE AND LOCAL REGULATIONS .TREAT AS HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
ass
ume responsibility for the suitability of this information to their
particular situation.