

SULFLO,INC. -- MIL-L-9000 DIESEL ENGINE OIL -- 9150-00-181-8097

=====
Product Identification
=====

Product ID:MIL-L-9000 DIESEL ENGINE OIL

MSDS Date:07/01/1988

FSC:9150

NIIN:00-181-8097

MSDS Number: BDGPM

=== Responsible Party ===

Company Name:SULFLO,INC.

Address:1158 ERIE AVE.

Box:285

City:NORTH TONAWANDA

State:NY

ZIP:14120-3507

Info Phone Num:716-695-3585

Emergency Phone Num:716-695-3585

Prepar

er's Name:THOMAS G. MUSILLI

CAGE:KO495

=== Contractor Identification ===

Company Name:SULFLO INC

Address:1158 ERIE AVE

Box:285

City:NORTH TONAWANDA

State:NY

ZIP:14120-3507

Country:US

Phone:716-695-3585

CAGE:1V074

Company Name:SULFLO,INC.

Address:1158 ERIE AVE.

Box:285

City:NORTH TONAWANDA

State:NY

ZIP:14120-3507

Phone:716-695-3585

CAGE:KO495

=====
Composition/Information on Ingredients
=====

Ingred Name:300 HIV NEUTRAL OIL

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: 61.7

%
OSHA PEL:5 MG/CUM OIL MIST
ACGIH TLV:5 MG/CUM OIL MIST

Ingred Name:BRIGHT STOCK
CAS:64742-57-0
Fraction by Wt: 25.0%

Ingred Name:LUBRIZOL 1161
Fraction by Wt: 13.3%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRODUCT IS A MILD IRRITANT. MFR CLAIMS
YEARS OF USE WITH NO KNOWN ILL EFFECTS.
Explanation of Carcinogenicity:"USED
GASOLINE ENGINE OIL" HAS BEEN
DECLARED A CARCINOGEN BY IARC.
Effects of Overexposure:PRODUCT MAY PRODUCE A MILD CONTACT IRRITATION
TO EYES OR SKIN.
Medical Cond Aggravated by Exposure:NONE

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER 15 MIN. SKIN:REMOVE CONTAMINATED
CLOTHING AND LAUNDER BEFORE REUSE. WASH WITH SOAP & WATER.
INHALED:REMOVE FROM EXPOSURE. INGESTED:DO NOT INDUCE VOMITING. GET
MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:400F/204C
Autoignition Temp:Autoignition Temp Text:450F
Extinguishing Media:WATER FOG,CARBON DIOXIDE,DRY
CHEMICAL,FOAM,EARTH/SAND.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. WATER
MAY CAUSE FROTHING AND/OR SPREAD FIRE.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH SAND OR INERT

MATERIAL.
Neutralizing Agent:NONE

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL AREA FREE FORM SPARKS &
OPEN FLAMES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE SHOULD BE NEEDED. USE NIOSH RESPIRATOR FOR
ORGANIC MISTS/VAPORS IF TLV IS EXCEEDED.

Ventilation:NORMAL ROOM VENTILATION

Protective Gloves:NEOPRENE,POLYETHYLENE

Eye Protection:SAFETY GLASSES

Other Protectiv

e Equipment:WEAR PROTECTIVE CLOTHING OF
RUBBER/POLYETHYLENE FOR HIGH SPLASH HAZARD. NONE NEEDED UNDER
NORMAL USE.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:V6

Boiling Pt:B.P. Text:700F/371C

Spec Gravity:0.88

Solubility in Water:NIL

Appearance and Odor:OILY LIQUID,BLAND ODOR

=====
Stability and Reactivity Data
=====

Stability Indicator/M

aterials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:NORMAL PRODUCTS OF COMBUSTION.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.
MFR SUGGESTS INCINERATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no

manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.