

DEFT INC CHEMICAL COATING DIV -- 03-BL-48 DEFTHANE -- 8010-00-181-8284

=====  
Product Identification  
=====

Product ID:03-BL-48 DEFTHANE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-181-8284

Kit Part:Y

MSDS Number: BDGTQ

=== Responsible Party ===

Company Name:DEFT INC CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Info Phone Num:714-474-0400

Emergency Phone

Num:800-424-9300 CHEMTREC

CAGE:33461

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: 20%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA

III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 15%  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)  
CAS:111-15-9  
RTECS #:KK8225000  
Fraction by Wt: 20%  
OSHA PEL:S,100 PPM  
ACGIH TLV:S, 5 PPM; 9192

=====  
===== Hazards Identification =====

Effects of Overexposure:MODERATE EYE IRRITANT.POSSIBLE SKIN IRRITANT.  
INHALATION-IRRITATION OR NARCOSIS

=====  
===== First Aid Measures =====

First Aid:SKIN-WIPE WITH CLOTH THEN RINSE WITH WATER & WASH WITH SOAP  
AND WATER. EYE-FLUSH 10 MIN. WITH WATER. CONSULT PHYSICIAN.  
INHALATION-REMOVE TO FRESH AIR

=====  
===== Fire Fighting Measures =====

Flash Point:28F;-2C TOC  
Lower Limits:1.6  
Extinguishing Media:CO\*2,FOAM OR DRY CHEMICAL  
Fire Fighting Procedures:WEAR RESPIRTOR. DO NOT USE WATER STREAM  
Unusual Fire/Explosion Hazard:DO NOT APPLY TO  
HOT SURFACES.DO NOT USE  
NEAR SPARKS OR OPEN FLAMES

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH OIL ABSORBING COMPOUND OR DRY  
RAGS.FLUSH WITH LARGE VOLUME OF WATER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:MATERIA IS MOISTURE SENSITIVE. KEEP IN  
TIGHTLY CLOSED CONTAINERS  
Other Precautions:AVOID PROLONGED INHALATION. IF VENTILATION IS POOR  
USE FRESH AIR SUPPL

# Y MASK

## ===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST FAN

Protective Gloves:YES

Eye Protection:YES

Other Protective Equipment:CARTRIDGE TYPE RESPIRTOR-MSC CATALOG NO  
CR84306

Supplemental Safety and Health

B.P.RANGE:79-164C \* PART A OF 2 COMPONENT SYSTEM

## ===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-331F

Vapor Pres:26

Vapor Density:>1

Spec Gravity:1.03

Evaporation Rate & Reference:< E

THER

Solubility in Water:INSOLUBLE

Appearance and Odor:BLUE-PAINT;ODOR PLEASANT, PUNGENT

Percent Volatiles by Volume:70.9

## ===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, ALCOHOLS AND OTHER COMPOUNDS REACTIVE WITH ISOCYANATE

Stability Condition to Avoid:SPARKS, STATIC ELECTRICITY, OPEN FLAME OR  
HEAT

## ===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN TIGHTLY CLOSED CO  
NTAINER AND

FINALLY BY SANITARY LANDFILL

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of

this information to their particular situation.