

PHIPPS PRODUCTS CORPORATION -- ACETONE -- 6810-00-184-4796

=====
Product Identification
=====

Product ID:ACETONE

MSDS Date:01/01/1985

FSC:6810

NIIN:00-184-4796

MSDS Number: BDGXT

=== Responsible Party ===

Company Name:PHIPPS PRODUCTS CORPORATION

Address:186 LINCOLN ST SUITE 502

City:BOSTON

State:MA

ZIP:02111-2403

Country:US

CAGE:86511

=== Contractor Identification ===

Company Name:PHIPPS PRODUCTS
CORP

Address:186 LINCOLN ST SUITE 502

Box:City:BOSTON

State:MA

ZIP:02111-2403

Country:US

Phone:OUT OF BUSINESS

CAGE:86511

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 100%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:PRODUCES A STATE OF STUPOR.

=====

===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR. SKIN CONTACT IS ONLY A SLIGHT HAZARD;
HOWEVER, SKIN SHOULD BE FLUSHED WITH WATER. MODERATE HAZARD TO THE
EYE, BUT LIQUID CONTACT SHOULD BE TREATED WITH FLUSHING OF EYE WITH
WATER FOR 15 MINUTES.

===== Fire Fighting Measures =====

Flash Point:4F TOC(-3F TCC)
Lower Limits:2.6
Upper Limits:12.8
Extinguishing Media:CO*2 OR DRY CHEMICAL FOR SML FIRES-FOAM FOR LG

FIRES.

Fire Fighting Procedures:DILUTION OF BURNING LIQUID WITH WATER WILL
EFFECT EXTINGUISH

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. FLUSH
HEAVILY WITH WATER.

===== Handling and Storage =====

Handling and Storage Precautions:ELIMINATE ALL SOURCES OF IGNITION. USE
WITH ADEQUATE VENTILATION. DO NOT LEAVE CONTAINER OPEN. A
VOID

PROLONGED OR REPEATED CONTACT WITH SKIN.

Other Precautions:DO NOT USE COPPER.WEAR RUBBER GLOVES,RUBBER
APRONS,CHEMICAL GOGGLES,SELF-CONTAINED BREATHING APPARATUS OR HOSE
MASK WITH BLOWER,FULL MASK FACE PIECE. DO NOT SHIP
W/FOODS,EXPLOSIVES,OXIDIZERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FULL FACE MASK WITH ORGANIC CHEMICAL CANISTER OR
SUPPLIED AIR.

Ventilation:LOCAL EXHAUST IS PREFERRED. MECHANICAL IS ACCEPTABLE.

Pr

Protective Gloves: RUBBER
Eye Protection: FACE SHIELD
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: F2
Boiling Pt: B.P. Text: 133F
Vapor Pres: 186
Vapor Density: 2.0
Spec Gravity: 0.7905
Evaporation Rate & Reference: 14.48, BUTYL ACET.
Solubility in Water: COMPLETE
Appearance and Odor: HIGHLY FLAMMABLE LIQUID; SHARP, PENETRATING ODOR.
Percent Volatiles by Volume: 99.9

===== Stability and Reactivity Data =====

Stability

Indicator/Materials to Avoid: YES
CATALYSTS SUCH AS BA (OH)², NAOH & OTHER ALKALIES; H²SO⁴.
Stability Condition to Avoid: LOW TEMPERATURES.
Hazardous Decomposition Products: NONE
Conditions to Avoid Polymerization: LOW TEMPERATURES IN PRESENCE OF
CATALYSTS-COND. WILL OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods: ATOMIZE INTO AN INCINERATOR UNDER APPROVED
CONTROLLED PROCEDURES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.