

SULFLO INCORPORATED -- VVG-671E GRADE#1,#2 -- 9150-00-190-0919

===== Product Identification =====

Product ID:VVG-671E GRADE#1,#2

MSDS Date:01/01/1987

FSC:9150

NIIN:00-190-0919

MSDS Number: BDHVG

=== Responsible Party ===

Company Name:SULFLO INCORPORATED

Address:1158 ERIE AVE

Box:285

City:N TONAWANDA

State:NY

ZIP:14120-3507

Country:US

Emergency Phone Num:(716)695-3585

CAGE:KO552

=== Contractor Ide

ntification ===

Company Name:SULFLO INC

Address:1158 ERIE AVE

Box:285

City:NORTH TONAWANDA

State:NY

ZIP:14120-3507

Country:US

Phone:716-695-3585

CAGE:1V074

Company Name:SULFLO INCORPORATED

Address:1158 ERIE AVE

Box:285

City:N TONAWANDA

State:NY

ZIP:14120-3507

Country:US

CAGE:KO552

===== Composition/Information on Ingredients =====

Ingred Name:CALCIUM STEARATE

CAS:1592-23-0

RTECS #:WI3000000

ACGIH TLV:NOT SPECIFIED

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CA

S:8012-95-1
RTECS #:PY8030000
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3/10 STEL;9192

=====
Hazards Identification
=====

Effects of Overexposure:PER MFR,NO ILL EFFECTS DUE TO ITS USE.MAY IRRITATE EYES AND SKIN.USE PERSONAL HYGIENE.

=====
First Aid Measures
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREA
THING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

=====
Fire Fighting Measures
=====

Flash Point:350F/177C (OC)
Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,SAND,FOG.
Fire Fighting Procedures:USE NIOSH APPROVED SCBA IN FIRES AND IN
CONFINED AREA
Unusual Fire/Explosion Hazard:NONE NOTED BY THE MFR.USE REASONABLE
CARE,COMBUSTIBLE MATERIAL.

=====
Accidental Release Measures
=====

Spill Release Procedures:USE PROPER PERSO
NAL PROTECTION.USE SUITABLE
ABSORBENT AND RECOVER FOR PROPER DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED
AREA.KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.
Other Precautions:AVOID CONTACT WITH SKIN AND EYES.WASH AFTER EACH USE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS
OR OIL MIS

T

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:OIL RESISTANT

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:700F/371C

Vapor Pres:.01

Vapor Density:0.0

Spec Gravity:0.9

Evaporation Rate & Reference:0.01 (BUT.ACET=1)

Solubility in Water:N

EGLIGIBLE

Appearance and Odor:SEMI-SOLID BUTTERY LUBRICATING GREASE-BLAND.

Percent Volatiles by Volume:0.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NATURAL RUBBER

Stability Condition to Avoid:NONE NOTED BY THE MFR

Hazardous Decomposition Products:CO IF INCOMPLETE COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,S

TATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informati

on to their
particular situation.