

EATON CORP,POWER CONTROL OPERATIONS -- 48-1604-5 -- 6110-00-204-3271

=====  
Product Identification  
=====

Product ID:48-1604-5

MSDS Date:01/01/1985

FSC:6110

NIIN:00-204-3271

MSDS Number: BDJLX

=== Responsible Party ===

Company Name:EATON CORP,POWER CONTROL OPERATIONS

Address:4265 N 30TH ST

City:MILWAUKEE

State:WI

ZIP:53216-1894

Country:US

CAGE:KO400

=== Contractor Identification ===

Company Name:EAT

ON CORP SPECIFIC INDUSTRY CONTROL DIV

Address:4265 N 30TH ST

Box:City:MILWAUKEE

State:WI

ZIP:53216-1894

Country:US

Phone:414-358-1720

CAGE:27192

Company Name:EATON CORP,POWER CONTROL OPERATIONS

Address:4265 N 30TH ST

Box:City:MILWAUKEE

State:WI

ZIP:53216-1894

Country:US

CAGE:KO400

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OSHA PEL, SEE  
29CFR 1910.1101)

CAS:1332-21-4

RTECS #:CI6475000

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:0.5 FIBERS/CC; A1;89

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====  
Hazards Identification =====

Effects of Overexposure:ASBESTOS DUST IS KNOWN HUMAN CARCINOGEN.ALSO  
COUGH,SHORT OF BREATH,WEAKNESS,CYANOSIS,ETC.

=====  
First Aid Measures =====

First Aid:SKIN:CONSULT DOCTOR FOR DERMATITIS.EYES:FLUSH WITH WATER  
FOLLOWED BY TREATMENTS OF OPHTHALMOLOGIST.INHALATION:CONSULT  
PHYSICIAN AT ONCE.

=====  
Fire Fighting Measures =====

Extinguishing Media:EXTINGUISH W. AGENT SUITABLE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP

=====  
Accidental Release Measures =====

Spill Release Procedures:PICK UP MATERIAL & RETURN TO CONTAINER.IF ANY  
BROKEN MTERIAL EXISTS,BE CAREFUL TO AVOID DUSTING CONDITIONS.PLACE  
BROKEN MATERIAL INTO A SEALED CONTAINER.VACUUM OR WET CLEAN ONLY.DO  
NOT DRY SWEEP.

=====  
Handling and Storage =====

Handling and Storage Precautions:AVOID CUTTING OR GRINDING ON  
ITEM.AVOID ANY DUSTING CONDITIONS.MAINTAIN GOOD HOUSEKEEPING.

=====  
Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED DUST MASK AS A MINIMUM.SELF CONT  
APP FOR DUSTING COND

Ventilation:PROVIDE GOOD LOCAL VENTILATION TO KEEP BELOW PEL

Protective Gloves:WORKING GLOVES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:FULL WORK

CLOTHING TO PREVENT REPEATED OR  
PROLONGED CONTACT.

Supplemental Safety and Health

SAFETY DATA DEVELOPED BY DGSC-STF.STORAGE CODE BASED ON FACT THAT  
ASBESTOS IS BOUND UP & NOT LOOSE.

===== Physical/Chemical Properties =====

HCC:T6

Appearance and Odor:ASBESTOS FIBERS IN BOUND FORM IN FRICTION LINING.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN

Hazardous Decomposition Products:NONE

KNOWN

===== Disposal Considerations =====

Waste Disposal Methods:PLACE IN SEALED PLASTIC BAG OR  
CONTAINER.ULTIMATE DISPOSAL MUST COMPLY WITH ALL LOCAL,STATE &  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and

d

disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.