View NSN Online: https://aerobasegroup.de/nsn/3040-00-204-3271

EATON CORP, POWER CONTROL OPERATIONS -- 48-1604-5 -- 6110-00-204-3271

========= Product Identification ============

Product ID:48-1604-5 MSDS Date:01/01/1985

FSC:6110

NIIN:00-204-3271

MSDS Number: BDJLX === Responsible Party ===

Company Name: EATON CORP, POWER CONTROL OPERATIONS

Address:4265 N 30TH ST

City:MILWAUKEE

State:WI

ZIP:53216-1894 Country:US CAGE:KO400

=== Contractor Identification ===

Company Name: EAT

ON CORP SPECIFIC INDUSTRY CONTROL DIV

Address:4265 N 30TH ST Box:City:MILWAUKEE

State:WI

ZIP:53216-1894 Country:US

Phone:414-358-1720

CAGE:27192

Company Name: EATON CORP, POWER CONTROL OPERATIONS

Address:4265 N 30TH ST Box:City:MILWAUKEE

State:WI

ZIP:53216-1894 Country:US CAGE:KO400

====== Composition/Information on Ingredients ========

Ingred Name: ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OSHA PEL, SEE 29CFR 1910.1101)

CAS:1332-21-4 RTECS #:CI6475000

OSHA PEL:0.2 FIBERS/CC

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB ============= Hazards Identification ======================== Effects of Overexposure: ASBESTOS DUST IS KNOWN HUMAN CARCINOGEN. ALSO COUGH, SHORT OF BREATH, WEAKNESS, CYANOSIS, ETC. First Aid:SKIN:CONSULT DOCTOR FOR DERMATITIS.EYES:FLUSH WITH WATER FOLLOWED BY TREATMENTS OF OPHTHALMOLOGIST.INHALATION:CONSULT PHYSICIAN AT ONCE. _____ == Fire Fighting Measures ========== Extinguishing Media: EXTINQUISH W. AGENT SUITABLE FOR SURROUNDING FIRE. Fire Fighting Procedures: WEAR SELF-CNTND BRTHG APP ======== Accidental Release Measures ============= Spill Release Procedures: PICK UP MATERIAL & RETURN TO CONTAINER. IF ANY BROKEN MTERIAL EXISTS, BE CAREFUL TO AVOID DUSTING CONDITIONS. PLACE BROKEN MATERIAL INTO A SEALED CONTAINER. VACUUM OR WET CLEAN ONLY.DO NOT DRY SWEEP. _____ Handling and Storage ========== Handling and Storage Precautions: AVOID CUTTING OR GRINDING ON ITEM.AVOID ANY DUSTING CONDITIONS.MAINTAIN GOOD HOUSEKEEPING. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: NIOSH APPROVED DUST MASK AS A MINIMUM. SELF CONT APP FOR DUSTING COND Ventilation: PROVIDE GOOD LOCAL VENTILATION TO KEEP BELOW PEL Protective Gloves: WORKING GLOVES

ACGIH TLV:0.5 FIBERS/CC; A1;89

Eye Protection: SAFETY GLASSES

Other Protective Equipment: FULL WORK

CONTAINER.ULTIMATE DISPOSAL MUST COMPLY WITH ALL LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate an d

CLOTHING TO PREVENT REPEATED OR

PROLONGED CONTACT.
Supplemental Safety and Health

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.