

ROYAL LUBRICANTS CO., INC -- ROYCO 756D(BEFORE AUGUST 1980) -- 9150-00-223-4134

=====
Product Identification
=====

Product ID:ROYCO 756D(BEFORE AUGUST 1980)

MSDS Date:01/01/1985

FSC:9150

NIIN:00-223-4134

MSDS Number: BDKHT

=== Responsible Party ===

Company Name:ROYAL LUBRICANTS CO., INC

Emergency Phone Num:201-887-3100

CAGE:07950

=== Contractor Identification ===

Company Name:ROYAL LUBRICANTS COM

PANY INC.

Address:215 MERRY LN

Box:518

City:EAST HANOVER

State:NJ

ZIP:07936

Country:US

Phone:973-887-7411/7410

CAGE:07950

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 90%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ACRYLIC RESINS

Fraction by Wt: 8%

Ingred Name:TRICRESYL PHOSPHATE

CAS:1330-78-5

RTECS #:TD0175000

Fraction by Wt: 1%

Ingred Name:2,6-

DI-TERT-BUTYL-P-CRESOL
CAS:128-37-0
RTECS #:GO7875000
Fraction by Wt: 1%
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3; 9192

===== Hazards Identification =====

Effects of Overexposure:SLIGHT IRRITATION

===== First Aid Measures =====

First Aid:ORAL-DO NOT INDUCE VOMITING.EYES-WASH WITH COPIOUS QUANTITIES OF WATER.SKIN-REMOVE OIL BY WIPING FOLLOWED BY WASHING WITH SOAP & WATER

===== Fire Fighting Measures

=====

Flash Point:215F (COC)
Extinguishing Media:FOAM,CARBON DIOXIDE OR DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH CLAY DIATOMACEOUS EARTH, OR OTHER INERT MATERIALS

===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING OF OIL MIST

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED
Ventilation:LOCAL EXHAUST IF OIL MIST IS PRESENT
Eye Protection:GOGGLES FOR MISTING
Supplemental Safety and Health
THIS IS UPDATE OF HMIS ENTRY DATED 80050 FOR P/N ONLY;FOR MFR P/N 756E DATA,SEE P/N IND B THIS NSN.(P/N IND A IAW REVISION D & P/N B IAW REVISION E OF MIL-H-5606.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:600F
Spec Gravity:0.87
Solubility in Wa

ter:INSOLUBLE

Appearance and Odor:RED OIL WITH SLIGHT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS (LIQUID OXYGEN)

Hazardous Decomposition Products:FUMES,SMOKE & CARBON MONOXIDE FORMED
DURING COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:CONTROLLED BURNING OR APPROVED SOLID WASTE
DISPOSAL

Disclaimer (provided with this information by
the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.