

EXXON CO USA -- KUTWELL 30 -- 6850-00-224-9582

=====  
Product Identification  
=====

Product ID:KUTWELL 30  
MSDS Date:09/14/1987  
FSC:6850  
NIIN:00-224-9582  
MSDS Number: BDKMQ  
=== Responsible Party ===  
Company Name:EXXON CO USA  
Address:800 BELL STREET  
Box:2180  
City:HOUSTON  
State:TX  
ZIP:77252-2180  
Country:US  
Info Phone Num:713-656-2443  
Emergency Phone Num:713-656-3424  
CAGE:29667  
=== Contractor Identifica  
tion ===  
Company Name:CONVOY OIL CORP  
Address:1410 N FRONT STREET  
Box:29366  
City:PHILADELPHIA  
State:PA  
ZIP:19125  
Country:US  
Phone:215-739-5281  
CAGE:6A438  
Company Name:EXXON CO USA  
Address:800 BELL ST  
Box:2180  
City:HOUSTON  
State:TX  
ZIP:77252-2180  
Country:US  
Phone:713-656-6449  
CAGE:29667  
Company Name:EXXON COMPANY U.S.A.  
Address:Box:2180  
City:HOUSTON  
State:TX  
ZIP:77252-2180  
Country:US  
Phone:713-656-5949 / 713-656-3424  
CAGE:29700

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HYDROTREATED HEAVY NAPHTHENIC DISTILLATE, PETROLEUM  
CAS:64742-52-5  
RTECS #:PY8035000  
Fraction by Wt: >85%  
Other REC Limits:5 MG/M3 OIL MIST

Ingred Name:PROPRIETARY ADDITIVES  
Fraction by Wt: >15%  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE  
MILD SKIN IRRITATION.

===== First Aid Measures =====

First Aid:IN CASE OF  
SKIN CONTACT,WASH THOROUGHLY WITH SOAP& WARM  
WATER.IF SPLASHED INTO THE EYES,FLUSH W/CLEAR WTR FOR 15 MIN OR  
UNTIL IRRITATION SUBSIDES.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:315F,157C  
Lower Limits:0.9%  
Upper Limits:7%  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL F  
IRE EXPOSED  
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.  
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE  
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVR FREE LIQ.ADD ABS.TO SPILL AREA.KEEP  
PETROL.PRDCTS OUT OF SEWERS BY DIKING.ADVISE AUTHORITIESIF WTR HAS  
ENTERED OR MAY ENTER SEWERS OR LAND AREAS.

===== Handling and Storage =====

===

Handling and Storage Precautions:KEEP CNTNRS CLSD.DO NOT HANDL/STR.  
NEAR HT,FLAME,STRG.OXID.DO NOT CONTAMINATE FLUID.PROVD.BAFFLES ON  
MACHINS TO MINIMZ OIL MIST.  
Other Precautions:AVOID BRTHNG OIL MIST.REMOV.OIL SOAKD CLTHNG, AND  
LAUNDR BEFOR REUSE.DISCRD OIL-SOAKD SHOES. WASH SKIN THOROUGHLY  
W/SOAP & WATER AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMLY NOT NEEDED.USE SUPPLIED AIR RESP.  
PROTECTN IN ENCL  
SD SPACES.  
Ventilation:USE LOCL EXHAUST.PRVD.GRTR.THAN 60 FPM HOOD FOR ENCLSD SPCS  
Protective Gloves:CHEM.RESIST.GLV  
Eye Protection:SPLSH GOGGLS OR FACE SHLD  
Other Protective Equipment:CHEM.RESIST.APRON.  
Supplemental Safety and Health  
MSDS DATED 4-16-79./IBP:525F;FBP:885F.

===== Physical/Chemical Properties =====

HCC:N1  
Boiling Pt:B.P. Text:520F,271C  
Melt/Freeze Pt:M.P/F.P Text:-10F,-23C  
Vapor Pres:5  
Spec Gravity:0.9  
pH:9.7  
Evaporation Rate & Reference: