

DAVIS-HOLLAND OIL CORPORATION -- MIL-L-15019E,LUBRICATING OIL COMPOUNDED --  
9150-00-231-6646

=====  
Product Identification  
=====

Product ID:MIL-L-15019E,LUBRICATING OIL COMPOUNDED

MSDS Date:01/01/1985

FSC:9150

NIIN:00-231-6646

MSDS Number: BDKZF

=== Responsible Party ===

Company Name:DAVIS-HOLLAND OIL CORPORATION

Emergency Phone Num:716-473-6650

CAGE:KO727

=== Contractor Identification ===

Company

Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:DAVIS-HOLLAND OIL CORPORATION

CAGE:KO727

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM HYDROCARBONS

Fraction by Wt: 100%

=====  
Hazards Identification  
=====

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE  
MILD SKIN IRRITATION

=====  
= First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF  
NEED;EYES/SKIN:FLUSH W LG AMTS H\*2O FOR 15 MIN;INGEST:RINSE MOUTH;  
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER  
SYMPTOMS OF OVEREXPOSURE.

=====  
Fire Fighting Measures  
=====

Flash Point:560F COC

Lower Limits:1.0%

Upper Limits:6.0%

Extinguishing Media:FOAM,DRY CHEMICAL,CO\*2,WATER SPRAY OR FOG.

Fire Fighting Procedures:USE AIR-SUPPLD

RESCUE EQUIP;COOL EXPOS  
CONTNRS W/WATER.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK.  
EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT  
ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG  
SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

===== Handling and Storage =====  
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN  
USE.DO NOT HANDLE OR STORE NEAR HEAT,SPARKS,FLAMES OR STRONG  
OXIDANTS

Other Precautions:AVOID BREATHING OIL MIST.REMOVE OIL-SOAKED CLOTHING &  
LAUNDER BEFORE RE-USE.DISCARD OIL-SOAKED SHOES.WASH SKIN THOROUGHLY  
W/SOAP & WATER AFTER HANDLING;MFR NOTES TLV 5MG/CUM FOR OIL MIST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.IN CONFIN  
ED AREAS,USE  
SUPPLD-AIR RESPIRATR.

Ventilation:LOCAL EXHAUST TO CAPTURE FUMES & VAPORS

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:USE CHEM RESISTANT APRON OR OTHER CLOTHING  
IF NEEDED.

Supplemental Safety and Health

MSDS UNDATED;SPEC REFERENCE: MIL-L-15019E;MILITARY SYMBOL 6135.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:750F

Vapor Pres:.01

Vapor Density:>20

Spec Gravity:0.90

Evaporatio

n Rate & Reference: