

DELTA PETROLEUM COMPANY,INC. -- AVIATION OIL 6082D, 1065 GRADE -- 9150-00-231-6669
===== Product Identification =====

Product ID:AVIATION OIL 6082D, 1065 GRADE
MSDS Date:01/01/1987
FSC:9150
NIIN:00-231-6669
MSDS Number: BDLBN
=== Responsible Party ===
Company Name:DELTA PETROLEUM COMPANY,INC.
Emergency Phone Num:(504)833-2861
CAGE:7A348
=== Contractor Identification ===
Company Name:DELTA PETROLEUM CO., INC
Address:10352 RIVER ROAD,
Box:10397
City:ST. ROSE
State:LA
ZIP:70087
Country:US
Phone:504-832-2732
CAGE:7A348

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')
CAS:8012-95-1
RTECS #:PY8030000
Fraction by Wt: 92.5%
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVE PACKAGE CONTAINING SULFUR,NITROGEN; WT %
RANGE:5-10%
Fraction by Wt: 07.5%

===== Hazards Identificatio

n =====

Effects of Overexposure:LOW ORDER OF TOXICITY AND IRRITANCY.MAY BE IRRITANT TO SKIN OR EYES ON PROLONGED EXPOSURE.

===== First Aid Measures =====

First Aid:EYE CONTACT:FLUSH PROMPTLY WITH LARGE QUANTITIES OF WATER UNTIL ANY IRRITATION SUBSIDES.SKIN CONTACT:-WASH WITH MILD SOAP & WATE.IN CASE OF INGESTION,CALL A DOCTOR.

===== Fire Fighting Measures =====

Flash Point:440F/227C (COC)

Ex

tinguishing Media:FOAM,DRY CHEMICAL,WATERSPRAY,WATERFOG,CARBON DIOXIDE

Fire Fighting Procedures:USE WATERSPRAY TO COOL FIRE EXPOSED SURFACES.

Unusual Fire/Explosion Hazard:RESPIRATORY PROTECTION REQUIRED FOR FIRE FIGHTING PERSONNEL

===== Accidental Release Measures =====

Spill Release Procedures:KEEP PUBLIC AWAY. SHUT OFF SOURCE IF POSSIBLE.DIKE WITH SAND OR EARTH.NOTIFY LOCAL AUTHORITIES OR POLICE IF THE PRODUCT HAS ENTERED A WATER COURSE OR SEWER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE.KEEP AWAY FROM HEAT AND OPEN FLAMES.DO NOT STORE NEAR FLAME OR STRONG OXIDIZING AGENTS.

Other Precautions:AVOID EYE CONTACT AND PROLONGED OR REPEATED SKIN CONTACT. AVOID BREATHING OIL MIST,WASH OFF AFTER HANDLING

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQMNTS UNDER ORDINARY CO

NDITIONS/ADEQUATE VENT.

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:NEOPRENE

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Supplemental Safety and Health

MSDS FROM DELTA PETROLEUM CO DATED 11/1/85; SPEC REF: MIL-L-6082D, TYPE II, GRADE 1065

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:500F(260C)

Vapor Pres:1.0

Spec Gravity:0.9007

E

vaporation Rate & Reference:NEGLIGIBLE
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BRIGHT & CLEAR LIQUID (OIL),MILD ODOR.
Percent Volatiles by Volume:NEGL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:NONE SPECIFIED BY THE MFR.
Hazardous Decomposition Products:CO, CO*2, ALDEHYDES,KETONES & OXIDES
OF NITROGEN & SULFUR.

===== Disposal Consideration

s =====

Waste Disposal Methods:CONTAIN WITH A SUITABLE ABSORBANT,RECOVERED
MATERIAL CAN BE INCINERATED OR DISPOSED OF IN ACCORDANCE
WITH,LOCAL,STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability
y for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.