

SULFLO INC. -- VV-L-800C;LUBRICATING OIL;CODE:10851 -- 9150-00-231-6689

=====
Product Identification
=====

Product ID:VV-L-800C;LUBRICATING OIL;CODE:10851

MSDS Date:11/17/1986

FSC:9150

NIIN:00-231-6689

MSDS Number: BDLCC

=== Responsible Party ===

Company Name:SULFLO INC.

Address:1158 ERIE AVE

City:NORTH TONAWANDA

State:NY

ZIP:14120-3507

Country:US

Emergency Phone Num:716-695-3585

Preparer's Name:

THOMAS G. MUSILLI

CAGE:JO986

=== Contractor Identification ===

Company Name:SULFLO INC

Address:1158 ERIE AVE

Box:285

City:NORTH TONAWANDA

State:NY

ZIP:14120-3507

Country:US

Phone:716-695-3585

CAGE:1V074

Company Name:SULFLO INC.

Address:1158 ERIE AVE

Box:285

City:NORTH TONAWANDA

State:NY

ZIP:14120-3507

Country:US

Phone:716-695-3585

CAGE:JO986

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL

CAS:64742-53-6

RTECS #:PY8036000

Fraction by Wt: 97.0%

ACGIH

TLV:5MG/CUM(OIL MIST)

Ingred Name:BARIUM SULFONATE

CAS:25619-56-1

RTECS #:CR0700000

Fraction by Wt: 02.0%

OSHA PEL:0.5 MG/M3 (BA)

ACGIH TLV:0.5 MG/M3 (BA); 8990

Ingred Name:ZINC DIAMYL DITHIOCARBAMATE

CAS:15337-18-5

Fraction by Wt: 01.0%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:PER MSDS,THIS PRODUCT HAS NO ILL EFFECTS KNOWN TO MFR;MAY IRRITATE EYES AND SKIN.

Effe

cts of Overexposure:PER MFR,NO KNOWN ILL EFFECTS.MAY IRRITATE EYES & SKIN.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF

NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

=====
===== Fire Fighting Measures =====

FI

ash Point Method:TCC

Flash Point:380F/193C

Autoignition Temp:Autoignition Temp Text:430F

Extinguishing Media:WATERFOG,CO*2,DRY CHEMICAL,FOAM,EARTH OR SAND.

Fire Fighting Procedures:WATERMAY CAUSE FROTHING:USE NIOSH APPROVED SCBA IN CONFINED.

Unusual Fire/Explosion Hazard:NONE NOTED;USE REASONABLE CAR.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;ABSORB WITH SAND OR INERT MATERIAL&SWEEP OR SCOOP UP INTO A CON

TAINER FOR
PROPER DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA.KEEP AWAY FROM SPARKS & OPEN FLAMES.WASH THOROUGHLY AFTER EACH USE.

Other Precautions:AVOID CONTACT WITH SKIN & EYES.DO NOT BREATHE VAPORS/MIST.DO NOT USE CONTAMINATED CLOTHES.

=====
Exposure Controls/Personal Protection
=====

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE

VENTILATION

Protective Gloves:NEOPRENE

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:V6

Boiling Pt:B.P. Text:700F/371C

Spec Gravity:0.90

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER OIL-BLAND

Percent Volatiles by Volume:0.0

=====
Stability and Reactivity Data
=====

Stabi

lity Indicator/Materials to Avoid:YES

STRONG OXIDIZER

Stability Condition to Avoid:OPEN FLAMES

Hazardous Decomposition Products:OXIDES OF CARBON AND SULFUR.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The

United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.